


Combination Wrench



- Forged with quality Cr-V with high durability
- Electroplated matte surface with texture
- Suitable for auto maintenance

No.	Spec. (mm)	L(mm)	H(mm)	S(mm)	D(mm)	B(mm)			
40504	8	112	10.0	8.15	16.5	14.4	6	96	3.3
40505	9	123	10.0	9.15	18.2	16.3	6	96	3.8
40506	10	131	10.5	10.1	20.5	16.3	6	96	4.5
40507	11	147.6	11.8	11.1	22.6	17.8	6	36	2.3
40508	12	155	12.8	12.1	24.5	19.4	6	36	3
40509	13	164	13.0	13.1	26.7	21	6	36	3.5
40510	14	182	15.3	14.2	28.8	22.3	6	36	4.5
40511	15	192	15.5	15.2	30.8	23.7	6	36	5.2
40512	16	202	15.9	16.2	32.8	24.5	6	36	5.9
40513	17	223	16.7	17.2	35.1	27.8	6	36	7
40514	18	236	17.4	18.2	37	28.5	4	24	5.2
40515	19	245	17.8	19.2	39	29.6	6	36	8.9
40516	21	271	18.7	21.2	43	32	4	24	7.6
40517	22	296	18.7	22.2	45	34	4	24	8
40518	24	322	19.6	24.3	49	36	4	24	10.2

Oil Filter Wrench



No.	Spec. (mm)			
97427	55-75	12	24	7.3
97428	75-95	12	24	8.4

▲ Excluded from lifetime warranty terms.

Cross Lug Wrench




- Cr-V material forged
- 3pc. Socket End (17, 19, 21mm) and 1pc. 1/2" Drive End

No.	Spec.			
48101	16"	-	12	164
48102	20"	-	12	20.8

▲ Excluded from lifetime warranty terms.

98111 Tyre Inflator



- Avoiding wetted from water and impacted
- After continuous inflating 10 mins, cool 15min at least
- After connecting the pipeline connector, manually turn on or off the switch
- When there is abnormal noise in inflation, please turn off the machine and send it to the after-sales outlet for repair

No.	Rated Voltage	Air output	Rated Power	Max. Pressure	Output Current	Pressure Precision			
98111	DC12V	30L/min	120W	6Bar	10A	+ 2Psi	-	12	20.8

▲ Excluded from lifetime warranty terms.

97106 Round Point Finishing Hammer 260g



Operating Instructions

- Capable of marking tire puncture and pulling out the debris
- Capable of finding out puncture direction via spiral needle and inserting it to remove debris
- Capable of repairing tire by inserting the rubber strip into the crochet needle by 2/3 in length along the hole, rotating 360°.
- Pulling it out and cutting off the remaining rubber strip

No.			
97106	10	40	8.8

▲ Excluded from lifetime warranty terms.