

LECM / LECMS Plastic Clamp Levers - Miniature Type, Male Screw







- *1: Setscrew head shapes have been changed from hex sockets to hexalobular sockets.
- Material/Finish

	LECM Made of Steel	LECMS Made of Stainless Steel
Lever Part	Nylon 6 (Various Color)	Nylon 6 (Various Color)
Thread Part	SUM22L Ferrosoferric Oxide Film (Black)	SUS303
Setscrew	Steel Ferrosoferric Oxide Film (Black)	Stainless Steel
Serration Ring	Zinc Die Cast	Zinc Die Cast

Stainless Steel Wire or SWPB



- The product development was conducted with LCA, Life Cycle Assessment, in consideration for environmental load, especially for global warming.
- Greenhouse effect gas emission is reduced by 6.5
 compared to conventional products.
- A serration ring made of zinc die cast is inserted into the lever body made of plastic. They also realize sufficient strength for fitting with metal thread serration.
- Female screw type LECF LECFS with the same shape is available. ⇒ P.xxxx
- There are five color variations. They can be selected by the end symbol of the part number.

	-
End Symbol 13	Lever Part Color
вк	Matte black
SG	Matte Silver
OR	Matte orange
YW	Matte yellow
SK	Matte Transparent

• Part number specification

LECMS-3 - 16 - SK

For **1** screw length Lm, select from the sizes marked with **●** in the table.

Dimensions

Spring

Unit:mm

Available / Add'l charge

	Part Number 1	M (Coarse)									Number	Max. load*1	Max. clamping*1	
		Nominal of Thread	Pitch		Н	H'	h	S	D	d	of Teeth	(N)	force (kN)	Mass (g)
LECM-3	LECMS-3	M3	0.5	30	29	32.5	24.5	4.2	13	10	18	13	0.95	14 - 15
LECM-4	LECMS-4	M4	0.7	30	29	32.5	24.5	4.2	13	10	18	31	1.7	15 - 16
LECM-5	LECMS-5	M5	8.0	30	29	32.5	24.5	4.2	13	10	18	62	2.7	16 - 20
LECM-6	LECMS-6	M6	1	30	29	32.5	24.5	4.2	13	10	18	110	3.8	16 - 22

*1: For the definitions of maximum load and maximum clamping force, see "Using the Clamp Lever / Tension Lever."

Stainless Steel Wire

RoHS

LECM Thread part : made of steel LECMS Thread part : made of stainless steel

Part Number	Lm (mm)	Lm(mm) 🔨											
	6	8	10	12	16	20	25	32	40	50			
LECM-3	•	•	•	•	•								
LECM-4			•	•	•	•	•	•					
LECM-5				•	•	•	•	•	•	•			
LECM-6				•	•	•	•	•	•	•			
LECMS-3	•	•	•	•	•								
LECMS-4			•	•	•	•	•	•					
LECMS-5				•	•	•	•	•	•	•			
LECMS-6				•	•	•	•	•	•	•			
Cleanroom Wach & Packaging - Down Screw Combination - Down Will Screw Length Adjustment - Down Willy Vibration Pecistant - Down Jaser Marking - Down													

Available / Add'l charge | Not Available

Please feel free to contact us