

Technical data


4T-30304A

Single row tapered roller bearings

Tapered roller bearing, pressed steel cage



VISUAL (S)



PRODUCT DEFINITION

Brand	NTN
d - Internal diameter	20 mm
D - External diameter	52 mm
B - Bearing/Inner ring width	16 mm
C - Outer ring width	13 mm
T - Total width	16,25 mm
d1 - External diameter inner ring	35 mm
a - Charge load application point	10,5 mm
rs - Min fillet radius	1,5 mm
r1s - Min fillet radius	1,5 mm
Mass	0,172 kg

PRODUCT PERFORMANCE

C - Dynamic load	39 kN
C0 - Static load	34 kN
Cu - Fatigue limit load	4,15 kN
A2 - Rating life coefficient	1
e - Coefficient	0.3
Y0 - Static axial load coefficient	1.1
Y2 - Upper axial load coefficient	2
N lim - Oil lubrication limit speed	11000 tr/min
N lim - Grease lubrication limit speed	8000 tr/min
Tmin - Min operating temperature	-40 °C
Tmax - Max operating temperature	120 °C



ABUTMENT

da max - Max shoulder diameter IR	28 mm
db min - Min IR shoulder diameter	28,5 mm
Da min - Min shoulder diameter OR	42,5 mm
Da max - Max shoulder diameter OR	43,5 mm
Db min - Min OR shoulder diameter	47,5 mm
Ca - Min clearance	3 mm
Cb - Min clearance	3 mm
ra max - Max fillet radius	1,5 mm
r1a - Max fillet radius	1,5 mm

INDUSTRY CALCUL FACTORS

Equivalent dynamic radial load

$$P = X \cdot Fr + Y \cdot Fa$$

$Fa / Fr \leq e$		$Fa / Fr > e$	
X	Y	X	Y
1	0	0.4	Y2

Equivalent static radial load

$$Po = Xo \cdot Fr + Yo \cdot Fa$$

Xo	Yo
0.5	Y0

If $Po \leq Fr$, then use $Po = Fr$

The values for e, Y2 and Y0 are shown in the above table



NTN Europe

1 rue des Usines · BP 2017 · 74010 Annecy Cedex · France · Tel. +33 (0)4 50 65 30 00
 S.A. au capital de 322 639 919 € · RCS ANNECY B 325 821 072 · Id. Fiscale : FR 48 325 821 072
 SIRET 325 821 072 00015 · Code APE 2815 Z · Code NACE 28.15