


DIN 46228

**NON-INSULATED
CORD END TERMINALS**



MAXIMUM ELECTRIC CURRENT:

A.W.G.	18	16	14
AMP.	17	18	30

TERMINAL MATERIAL: COPPER TUBE. (TIN PLATED)

WIRE RANGE A.W.G. mm ²	ITEM NO.	DIMENSION								CRIMPING TOOL
		L		D		C		W		
		inch	mm	inch	mm	inch	mm	inch	mm	
18 A.W.G. 1.0 mm ²	EN1006	.236	6.0							K.S. MODEL KST2000L WITH DIE INDEX NO:1 OR K.S. MODEL LY8-060 WITH DIE INDEX NO:1-1.5
	EN1007	.276	7.0							
	EN1008	.315	8.0							
	EN1010	.394	10.0							
	EN1012	.472	12.0	.067	1.7	.055	1.4	.098	2.5	
	EN1015	.591	15.0							
	EN1018	.709	18.0							
	EN1020	.787	20.0							
	EN1025	.984	25.0							
16 A.W.G. 1.5 mm ²	EN1506	.236	6.0							K.S. MODEL KST2000L WITH DIE INDEX NO:1.5 OR K.S. MODEL LY8-060 WITH DIE INDEX NO:1-1.5
	EN1507	.276	7.0							
	EN1508	.315	8.0							
	EN1510	.394	10.0							
	EN1512	.472	12.0	.079	2.0	.067	1.7	.110	2.8	
	EN1515	.591	15.0							
	EN1518	.709	18.0							
	EN1520	.787	20.0							
14 A.W.G. 2.5 mm ²	EN2506	.236	6.0							K.S. MODEL KST2000L WITH DIE INDEX NO:2.5 OR K.S. MODEL LY8-060 WITH DIE INDEX NO:2.5
	EN2507	.276	7.0							
	EN2508	.315	8.0							
	EN2510	.394	10.0	.102	2.6	.091	2.3	.134	3.4	
	EN2512	.472	12.0							
	EN2515	.591	15.0							