


DIN 46228

**NON-INSULATED
CORD END TERMINALS**



MAXIMUM ELECTRIC CURRENT:

A.W.G.	14	12	10	8
AMP.	15	35	50	70

TERMINAL MATERIAL: COPPER TUBE. (TIN PLATED)

WIRE RANGE A.W.G. mm ²	ITEM NO.	DIMENSION								CRIMPING TOOL
		L		D		C		W		
		inch	mm	inch	mm	inch	mm	inch	mm	
14 A.W.G. 2.5 mm ²	EN2518	.709	18.0	.102	2.6	.091	2.3	.134	3.4	K.S. MODEL KST2000L WITH DIE INDEX NO:2.5 OR K.S. MODEL LY8-060 WITH DIE INDEX NO:2.5
	EN2520	.787	20.0							
	EN2525	.984	25.0							
	EN2530	1.181	30.0							
12 A.W.G. 4 mm ²	EN4007	.276	7.0	.126	3.2	.110	2.8	.157	4.0	K.S. MODEL KST2000L WITH DIE INDEX NO:4 OR K.S. MODEL LY8-060 WITH DIE INDEX NO:4 OR WACO MODEL VARIOCRIMP 4
	EN4009	.354	9.0							
	EN4010	.394	10.0							
	EN4012	.472	12.0							
	EN4015	.591	15.0							
	EN4018	.709	18.0							
	EN4020	.787	20.0							
	EN4030	1.181	30.0							
10 A.W.G. 6 mm ²	EN6006	.236	6.0	.154	3.9	.138	3.5	.185	4.7	K.S. MODEL KST2000M WITH DIE INDEX NO:6 OR K.S. MODEL LY8-060 WITH DIE INDEX NO:6
	EN6010	.394	10.0							
	EN6012	.472	12.0							
	EN6015	.591	15.0							
	EN6018	.709	18.0							
	EN6020	.787	20.0							
	EN6025	.984	25.0							
8 A.W.G. 10 mm ²	EN10-6	.236	6.0	.193	4.9	.177	4.5	.228	5.8	K.S. MODEL KST2000M WITH DIE INDEX NO:10
	EN10-8	.315	8.0							
	EN10-12	.472	12.0							
	EN10-15	.591	15.0							