


DIN 46235

NON-INSULATED COPPER TUBULAR LUGS (TLD SERIES)


MAXIMUM ELECTRIC CURRENT:

A.W.G.	400	500	600	700	750	800	900	1000	1250	1500	1750	2000
AMP.	545	620	690	755	785	815	870	935	1065	1175	1280	1385

TERMINAL MATERIAL: COPPER TUBULAR

WIRE RANGE A.W.G. mm ²	ITEM NO.	DIMENSION mm									CRIMPING TOOL	Q'TY BOX
		a	b	C1	C2	d1	d2	d3	I	S		
400 MCM 240 mm ²	TLD12-240	40.0	42.0	16.0	13.0	21.5	13.0	29.0	92.0	6.5	NOVOPRESS MODEL HPM400	10
	TLD14-240			18.5	20.0		15.0					10
	TLD16-240			19.0	16.0		17.0					10
	TLD20-240		45.0	22.0	20.0		21.0					10
500 MCM 300 mm ²	TLD12-300	50.0	48.0	18.5	22.0	24.5	13.0	32.0	100.0	7.0	NOVOPRESS MODEL HPM400	5
	TLD14-300			18.5	22.0		15.0					5
	TLD16-300			19.0	16.0		17.0					5
	TLD20-300			22.0	20.0		21.0					5
600/750 MCM 400 mm ²	TLD14-400	70.0	55.0	23.0	27.0	27.5	15.0	38.5	115.0	10.0	NOVOPRESS MODEL HPM400	5
	TLD16-400			25.0	16.0		17.0					5
	TLD20-400				20.0		21.0					5
800/1000 MCM 500 mm ²	TLD16-500	70.0	60.0	23.0	27.0	31.0	17.0	42.0	125.0	10.0		5
	TLD20-500			25.0	20.0		21.0					5
1000/1250 MCM 625 mm ²	TLD20-625	80.0	60.0	25.0	20.0	34.5	21.0	44.0	135.0	10.0		2
1500/1750 MCM 800 mm ²	TLD20-800	100.0	75.0	25.0	20.0	40.0	21.0	52.0	165.0	12.0		2
2000 MCM 1000 mm ²	TLD20-1000	100.0	85.0	25.0	20.0	44.0	21.0	58.0	165.0	14.0		2