

NYLON-FULLY INSULATED TWIN WIRE MALE DISCONNECTORS (TA TYPE)

MAXIMUM ELECTRIC CURRENT:

A.W.G.	22	20	18	16	14	12	10
AMP.	3	4	7	10	15	20	24

MAXIMUM ELECTRICAL RATING: 105°C 600 VOLTS MAX.


INSULATION MATERIAL: NYLON TERMINAL MATERIAL: BRASS

INSULATION COLOR:

22-18 A.W.G.: RED 16-14 A.W.G.: BLUE 12-10 A.W.G.: YELLOW

TERMINAL BARREL I.D.:

22-18 A.W.G.: C=1.7mm 16-14 A.W.G.: C=2.3mm 12-10 A.W.G.: C=3.4mm



WIRE RANGE A.W.G. mm ²	ITEM NO.	NEMA TAB	DIMENSION inch mm						CRIMPING TOOL	Q'TY BOX
			W	F	L	B	D	T		
22-18 A.W.G. 0.5-0.75 mm ²	MDFNY1-250TA	.032x.250 (0.8x6.35)	.250 6.35	.311 7.9	.945 24.0	.472 12.0	.244 6.2	.016 0.4		500
16-14 A.W.G. 1.5-2.5 mm ²	MDFNY2-250TA	.032x.250 (0.8x6.35)	.250 6.35	.311 7.9	.945 24.0	.472 12.0	.276 7.0	.016 0.4		500
12-10 A.W.G. 4-6 mm ²	MDFNY5-250TA	.032x.250 (0.8x6.35)	.250 6.35	.311 7.9	.945 24.0	.484 12.3	.331 8.4	.031 0.8		500