

Precision Screwdriver, Torx®



- Suitable for maintenance and repair of TV, clock, computer, glasses, communication instrument, optical instrument, video recorder, telephone, toy model, camera and all kinds of precision instrument and equipment
- Imported SVCM+ shank with heat treatment
- Matte-electroplated shank surface with phosphated and blackened tip for accuracy
- Rotary turncap adopted

No.	Spec. (mm)			
63012	T3x40	12	432	7.9
63013	T4x40	12	432	7.9
63001	T5x50	12	432	8
63002	T6x50	12	432	8.9
63003	T7x50	12	432	8.7
63004	T8x50	12	432	9.3
63005	T9x50	12	432	9.5
63008	T9x60	12	432	9.4
63006	T10x50	12	432	9.3
63007	T15x50	12	432	10.3
63009	T10x60	12	432	9.8
63010	T15x60	12	432	10.7
63011	T20x60	12	432	11.7

Precision Screwdriver, Hexagon



- Suitable for maintenance and repair of TV, clock, computer, glasses, communication instrument, optical instrument, video recorder, telephone, toy model, camera and all kinds of precision instrument and equipment
- Imported SVCM+ shank with heat treatment
- Matte-electroplated shank surface with phosphated and blackened tip for accuracy
- Rotary turncap adopted

No.	Spec. (mm)			
63101	0.67x40	12	432	7.8
63102	0.9x40	12	432	7.9
63103	1.3x50	12	432	8.1
63104	1.5x50	12	432	8.1
63105	2.0x50	12	432	6.5
63106	2.5x50	12	432	9.4
63112	2.5x75	12	432	10.3
63107	3.0x50	12	432	10.4
63113	3.0x75	12	432	11.4

Precision Screwdriver, Ball Point, Hexagon



- Suitable for maintenance and repair of TV, clock, computer, glasses, communication instrument, optical instrument, video recorder, telephone, toy model, camera and all kinds of precision instrument and equipment
- Imported SVCM+ shank with heat treatment
- Matte-electroplated shank surface with phosphated and blackened tip for accuracy
- Rotary turncap adopted

No.	Spec. (mm)			
63201	1.3x50	12	432	8.1
63202	1.5x50	12	432	8.9
63207	2.0x50	12	432	8.8
63210	2.5x75	12	432	10.3
63211	3.0x75	12	432	11.3

03371 ESD Nylon Toothbrush-Shaped Brush



- It is applicable to dust-free plant or laboratory in industries including electronics, communications, semiconductor and optics.
- This product can withstand normal cleaning agents such as gasoline, alcohol, acetone and Freon, without damage to appearance and performance.
- Performance parameters:
- Surface resistance of brush holder: <106Ω
- Surface resistance of bristle: <109Ω

Size/Specifications:

- Brush length × width: 175mm × 12mm
- Brush head length × width: 40mm × 12mm
- Bristle height: 18mm
- Arrangement of bristle: 8 holes/row × 2

No.			
03371	10	160	6.2

▲ Excluded from lifetime warranty terms.

03372 ESD Nylon U-Shaped Brush



- It is applicable to dust-free plant or laboratory in industries including electronics, communications, semiconductor and optics.
- This product can withstand normal cleaning agents such as gasoline, alcohol, acetone and Freon, without damage to appearance and performance.
- Performance parameters:
- Surface resistance of brush holder: <106Ω
- Surface resistance of bristle: <109Ω

Size/Specifications:

- Brush length × width: 115mm × 55mm
- Brush head length × width: 95mm × 45mm
- Bristle height: 25mm
- Arrangement of bristle: 14 holes/row × 7

No.			
03372	10	80	12.2

▲ Excluded from lifetime warranty terms.