

# Product datasheet

Specifications



## 13A 250V 1 Gang 3-Pin Universal Socket

KB413S

### Main

Product or component type	Socket-outlet
Device short name	KB426
Device presentation	Complete mechanism
Outlet standard	Universal
Colour tint	White

### Complementary

Outlet poles configuration	2P + E
Number of gangs	1 gang
Material	Polycarbonate: grid plate Polycarbonate: surround Nylon: base
Projecting depth	8 mm
Device mounting	Flush
Mounting support	Wall mounted
Fixing mode	By screw M3.5
Fixing center	60.3 mm
Embedding depth	35 mm
Rated current	13 A at 250 V AC, no inductive load
Network frequency	50 Hz
Contacts material	Brass and phosphor bronze
Connections - terminals	Pillar terminal
Terminal identifier	L N E
Tightening torque	0.4 N.m
Clamping connection capacity	2.5 mm <sup>2</sup> 4 mm <sup>2</sup>
Width	86 mm
Height	86 mm

## Environment

Ambient air temperature for operation -5...40 °C

Relative humidity 0...95 %

Environmental characteristic Indoor use

## Packing Units

Unit Type of Package 1 PCE

Number of Units in Package 1 1

Package 1 Height 8.6 cm

Package 1 Width 3 cm

Package 1 Length 8.6 cm

Package 1 Weight 108.6 g

Unit Type of Package 2 BB1

Number of Units in Package 2 10

Package 2 Height 15 cm

Package 2 Width 19 cm

Package 2 Length 10 cm

Package 2 Weight 1.156 kg

Unit Type of Package 3 CAR

Number of Units in Package 3 100

Package 3 Height 21 cm

Package 3 Width 31.5 cm

Package 3 Length 50 cm

Package 3 Weight 11108 g

## Offer Sustainability

Sustainable offer status Green Premium product

REACH Regulation [REACH Declaration](#)

REACH free of SVHC Yes

EU RoHS Directive Compliant  
[EU RoHS Declaration](#)

Toxic heavy metal free Yes

Mercury free Yes

China RoHS Regulation [China RoHS declaration](#)  
Pro-active China RoHS declaration (out of China RoHS legal scope)

RoHS exemption information Yes

Environmental Disclosure [Product Environmental Profile](#)

## Contractual warranty

Warranty 18 months

## Recommended replacement(s)