


CABLE TIES

LOCKING CABLE TIES




(*)Suffix "-WR" should be added if black(outdoor) color is required.

2.5 TIE BODY WIDTH	PART NO	Length	Width	Max	Tensile	Military	Installation	Package
		mm (inch)	mm (inch)	Bundle Dia,(inch)	Strength Kg(LBS)	Standard Spec,	TOOL Part No	Q' ty
	DACT 80-2.3-L	80 (3.1)	2.4 (.09)	17 (.68)	8.1 (18)	MS3367-4	DAG-50	1,000
	DACT100-2.5-L	100 (4.0)		21 (0.83)				
	DACT160-2.5-L	160 (6.2)	2.5 (.10)	40 (1.57)				
	DACT200-2.5-L	205 (8.0)		52 (2.02)				
3.6 TIE BODY WIDTH	DACT140-3.6-L	146 (5.7)	3.6 (.14)	35 (1.38)	17.8 (40)	MS3367-5	DAG-50	1,000
	DACT200-3.6-L	203 (8.0)		50 (2.00)				
	DACT210-3.6-L	210 (8.26)		52 (2.04)				
	DACT300-3.6-L	300 (11.8)		77 (3.03)				
	DACT370-3.6-L	370 (14.5)		102 (4.00)				

LOCKING CABLE TIES



(*)Suffix "-WR" should be added if black(outdoor) color is required.

4.8 TIE BODY WIDTH	PART NO	Length	Width	Max	Tensile	Military	Installation	Package
		mm (inch)	mm (inch)	Bundle Dia,(inch)	Strength Kg(LBS)	Standard Spec,	TOOL Part No	Q' ty
	DACT120-4.8-L	120 (4.7)	4.8 (.19)	30 (1.00)	22.2 (50)	MS3367-1	DAG-50	1,000
	DACT160-4.8-L	160 (6.2)		40 (1.57)		"		
	DACT190-4.8-L	190 (7.5)		48 (1.89)		"		
	DACT200-4.8-L	200 (8.0)		52 (2.05)		"		
	DACT250-4.8-L	250 (10.0)		67 (2.64)		MS3367-7		500
	DACT280-4.8-L	280 (11.0)		76 (2.99)				
	DACT300-4.8-L	300 (11.8)		83 (3.27)				
	DACT370-4.8-L	368 (14.5)		102 (4.02)				

Material : Nylon 66
 Color : Natural or Black(UV)
 Flammability : UL 94V-2 or UL94 V-0
 Service Temperature : 85 °C



Most **Dong-A Cable Ties**, when tested, meet the requirements of **MIL-S-23190E** (or **SAE AS23190**)

CABLE TIES

● LOCKING CABLE TIES




(*)Suffix "-WR" should be added if black(outdoor) color is required.

6.3 TIE BODY WIDTH	PART NO	Length mm (inch)	Width mm (inch)	Max Bundle Dia,(inch)	Tensile Strength Kg(LBS)	Military Standard Spec,	Installation TOOL Part No	Package Q' ty
	DAMCT270-6.1-L	279 (10.5)	6.1 (.24)	73 (2.87)		MS3367-3	DAG-250	500
	DAMCT300-6.3-L	300 (11.8)	6.3 (.24)	80 (3.15)	45.3 (100)			300
	DAMCT370-6.3-L	370 (14.5)	6.3 (.24)	102 (4.02)				
	DAMCT200-7.6-L	200 (8.0)		50 (2.00)		MS3367-3	DAG-250	500
	DAMCT300-7.6-L	300 (11.8)	7.6 (.30)	78 (3.07)	53.4kg (120)			300
	DAMCT370-7.6-L	370 (14.5)		102 (4.02)				

● LOCKING CABLE TIES



(*)Suffix "-WR" should be added if black(outdoor) color is required.

9.0 TIE BODY WIDTH	PART NO	Length mm (inch)	Width mm (inch)	Max Bundle Dia,(inch)	Tensile Strength Kg(LBS)	Military Standard Spec,	Installation TOOL Part No	Package Q' ty
	DAMCT450-9.0-L	455 (17.7)		127 (5.0)		MS3367-6	DAG-250	100
	DAMCT530-9.0-L	530 (20.9)		152 (6.0)				
	DAMCT650-9.0-L	650 (25.6)	9.0 (.35)	188 (7.40)	77.8 (175)			
	DAMCT780-9.0-L	780 (30.6)		225 (8.86)				
	DAMCT880-9.0-L	880 (34.6)		260 (10.24)				
	DAMCT1000-9.0-L	1000 (42.5)		320 (12.69)				

Material : Nylon 66
 Color : Natural or Black(UV)
 Flammability : UL 94V-2 or UL94 V-0
 Service Temperature : 85 °C

Most **Dong-A Cable Ties**, when tested, meet the requirements of **MIL-S-23190E** (or **SAE AS23190**)



CABLE TIES

EXTRA HEAVY LASHING TIES



Available only in Natural Color or Weather Resistant Black.


(*)Suffix "-WR" should be added if black(outdoor) color is required.

12.7 TIE BODY WIDTH	PART NO	Length mm (inch)	Width mm (inch)	Max Bundle Dia, (inch)	Tensile Strength Kg(LBS)	Military Standard Spec,	Installation TOOL Part No	Package Q' ty
	LOCKING TYPE  Loop on the head Type	DAL300-12.7-L	300 (11.8)	12.7 (.50)	70 (2.76)	110 (250)	MS3367-6	DAG-250
DAL400-12.7-L		400 (15.7)	102 (4.02)					
DAL540-12.7-L		540 (21.3)	150 (5.91)					
DAL780-12.7-L		780 (30.7)	220 (8.66)					
RELEASABLE TYPE  DARCT	DARCT300-12.7-L	300 (11.8)	12.7 (.50)	70 (2.76)	110 (250)	MS3367-6	DAG-250	100
	DARCT400-12.7-L	400 (15.7)		102 (4.02)				
	DARCT540-12.7-L	540 (21.3)		150 (5.91)				
	DARCT780-12.7-L	780 (30.7)		220 (8.66)				



Available only in Natural Color or Weather Resistant Black.

(*)Suffix "-WR" should be added if black(outdoor) color is required.

12.7 TIE BODY WIDTH	PART NO	Length mm (inch)	Width mm (inch)	Max Bundle Dia, (inch)	Tensile Strength Kg(LBS)	Military Standard Spec,	Installation TOOL Part No	Package Q' ty
	LOCKING TYPE  DAL	DAL300-12.7-L	300 (11.8)	12.7 (.50)	70 (2.76)	110 (250)	MS3367-6	DAG-250
DAL400-12.7-L		400 (15.7)	102 (4.02)					
DAL540-12.7-L		540 (21.3)	150 (5.91)					
DAL780-12.7-L		780 (30.7)	220 (8.66)					

※ 내한성(耐寒性) 재질 발주시는 "LT" 추가,
 내열성(耐熱性) 재질 발주시는 "HR" 추가,
 내후성(耐候性) 재질 발주시는 "WR" 추가 표시 바랍니다.
 (i.e) 내한성 : DAL400-12.7-LT
 내열성 : DAL300-12.7-HR
 내후성 : DAL300-12.7-LWR
 Service Temperature : 85°C

Most Dong-A Cable Ties, when tested, meet the requirements of MIL-S-23190E (or SAE AS23190)