

NYLON-INSULATED CORD END TERMINALS (E SERIES)


MAXIMUM ELECTRIC CURRENT:

A.W.G.	3/0	4/0	250	300
AMP.	310	360	405	445

MAXIMUM ELECTRICAL RATING: 105°C 600 VOLTS MAX.

CONNECTOR MATERIAL: COPPER TUBE.

INSULATION MATERIAL: NYLON



WIRE RANGE A.W.G. mm ²	ITEM NO.	DIMENSION inch mm						FRENCH COLOR	GERMAN COLOR	DIN COLOR	CRIMPING TOOL
		F	L	W	B	D	C				
3/0 A.W.G. 95 mm ²	E95-25	.984 25.0	1.732 44.0	.728 18.5	.748 19.0	.602 15.3	.571 14.5	RED 	RED 	RED 	K.S. MODEL KSTP-325-B WITH DIE INDEX NO:KC-95
	E95-30 ©	1.181 30.0	1.953 49.6								
4/0 A.W.G. 120 mm ²	E120-27	1.063 27.0	1.874 47.6	.799 20.3	.811 20.6	.697 17.7	.657 16.7	BLUE 	BLUE 	BLUE 	K.S. MODEL KSTP-325-B WITH DIE INDEX NO:KC-120
	E120-30 ©	1.181 30.0	2.008 51.0								
	E120-32	1.260 32.0	2.071 52.6								
	E120-34 ©	1.339 34.0	2.150 54.6								
	E120-48	1.890 48.0	2.228 56.6								
250/300 MCM 150 mm ²	E150-25	.984 25.0	1.992 50.6	.921 23.4	1.008 25.6	.811 20.6	.772 19.6	YELLOW 	YELLOW 	YELLOW 	K.S. MODEL KSTP-325-B WITH DIE INDEX NO:KC-150
	E150-27	1.063 27.0	2.071 52.6								
	E150-32	1.260 32.0	2.268 57.6								
	E150-38 ©	1.496 38.0	2.504 63.6								
	E150-58	2.283 58.0	3.291 83.6								



ALL LISTED

©: NOT RU AND C-RU LISTED