


NON-INSULATED COPPER TUBULAR LUGS (TLAF-AR SERIES)

MAXIMUM ELECTRIC CURRENT:

A.W.G.	8	6	4	2	1	1/0	2/0	3/0	4/0
AMP.	70	95	125	170	195	230	265	310	360

TERMINAL MATERIAL: COPPER TUBULAR

AR: STANDARD CHEMICAL TREATMENT(PREVENT ERODE)



WIRE RANGE A.W.G. mm ²	ITEM NO.	STUD SIZE		DIMENSION mm						CRIMPING TOOL	Q'TY BOX
		d2		W	d1	D	L	E	S		
8 A.W.G. 10 mm ²	TLAF10-5AR	#10	5.3	12.0	4.6	7.0	26.5	8.0	1.8	IZUMI MODEL 9H-60 WITH DIE INDEX NO : 8	500
	TLAF10-6AR	1/4	6.4	12.0	4.6	7.0	27.4	8.0	1.8		
	TLAF10-8AR	5/16	8.4	14.0	4.6	7.0	33.2	8.0	1.5		
	TLAF10-10AR	3/8	10.5	14.0	4.6	7.0	33.2	8.0	1.5		
	TLAF10-12AR	1/2	13.0	19.0	4.6	7.0	37.6	8.0	1.1		
6 A.W.G. 16 mm ²	TLAF16-5AR	#10	5.3	14.0	5.9	7.9	33.8	9.0	1.7	KLAUKE PK 25/2 WITH DIE INDEX: HD 25/16(8) OR NOVOPRESS MODEL HPM400 OR IZUMI MODEL 9H-60 WITH DIE INDEX NO : 14	500
	TLAF16-6AR	1/4	6.4								
	TLAF16-8AR	5/16	8.4								
	TLAF16-10AR	3/8	10.5								
	TLAF16-12AR	1/2	13.0	19.0	5.9	7.9	37.0	9.0	1.1		
4 A.W.G. 25 mm ²	TLAF25-5AR	#10	5.3	14.1	7.3	9.1	35.5	10.0	1.8	KLAUKE PK 25/2 WITH DIE INDEX: HD 25/25(10) OR NOVOPRESS MODEL HPM400 OR IZUMI MODEL 9H-60 WITH DIE INDEX NO : 14	250
	TLAF25-6AR	1/4	6.4								
	TLAF25-8AR	5/16	8.4								
	TLAF25-10AR	3/8	10.5								
	TLAF25-12AR	1/2	13.0	19.0	7.3	9.1	40.0	10.0	1.2		
2 A.W.G. 35 mm ²	TLAF35-6AR	1/4	6.4	16.5	8.6	11.0	43.3	16.0	2.3	KLAUKE PK 25/2 WITH DIE INDEX: HD 25/35(12) OR NOVOPRESS MODEL HPM400	100
	TLAF35-8AR	5/16	8.4								
	TLAF35-10AR	3/8	10.5								
	TLAF35-12AR	1/2	13.0	19.0							
1-1/0 A.W.G. 50 mm ²	TLAF50-6AR	1/4	6.4	19.0	10.6	13.0	47.0	16.0	2.5	KLAUKE PK 25/2 WITH DIE INDEX: HD 25/50(14) OR NOVOPRESS MODEL HPM400	100
	TLAF50-8AR	5/16	8.4								
	TLAF50-10AR	3/8	10.5								
	TLAF50-12AR	1/2	13.0								
2/0 A.W.G. 70 mm ²	TLAF70-6AR	1/4	6.4	21.0	11.7	14.3	52.0	18.5	2.6	KLAUKE PK 25/2 WITH DIE INDEX: HD 25/70(16) OR NOVOPRESS MODEL HPM400	50
	TLAF70-8AR	5/16	8.4								
	TLAF70-10AR	3/8	10.5								
	TLAF70-12AR	1/2	13.0								
3/0 A.W.G. 95 mm ²	TLAF95-6AR	1/4	6.4	23.1	13.2	15.8	57.0	17.0	2.8	KLAUKE PK 25/2 WITH DIE INDEX: HD 25/95(18) OR NOVOPRESS MODEL HPM400	50
	TLAF95-8AR	5/16	8.4								
	TLAF95-10AR	3/8	10.5								
	TLAF95-12AR	1/2	13.0								
4/0 A.W.G. 120 mm ²	TLAF120-6AR	1/4	6.4	25.4	14.2	17.2	59.0	17.0	3.0	KLAUKE PK 25/2 WITH DIE INDEX: HD 25/120(20) OR NOVOPRESS MODEL HPM400	25
	TLAF120-8AR	5/16	8.4								
	TLAF120-10AR	3/8	10.5								
	TLAF120-12AR	1/2	13.0								