

G Clamp



- Made by precision casting with high quality spheroidal cast iron, with electrostatic coating on surface
- Special reinforcement rib design, ensuring higher clamping force and safer use
- Precision machined screw rod, black finished surface, longer service life
- Special movable clamping head, ensuring effective clamping of workpiece and not easy to fall off

No.	Spec.			
90433	3"	6	24	17.8
90434	4"	4	16	17
90435	6"	6	12	20
90436	8"	1	8	18

▲ Excluded from lifetime warranty terms.

G series all steel T-handle F clamp



90452



90455

- Large clamping force: > 5000N
- Special tempering process, with good toughness of the force arm
- The groove design of the force arm increases the overall rigidity of the product

No.	L (mm)	Openness (mm)	Depth (mm)			
90451	271	200	100	10	-	-
90452	333	250	121	10	-	-
90453	388	301	141	10	-	-
90454	501	401	119	10	-	-
90455	588	501	120	5	-	-
90456	699	601	119	5	-	-
90457	911	801	120	5	-	-

▲ Life time warranty, except for screw rods, T-shaped handles, and gaskets.

90521 Manual Rivet Nut Tool



- Replaceable head for wide riveting range, suitable for the following rivet nuts
- M5(10-24), M6(1/4-20)
- M8(5/16-18), M10(3/8-16), M12(1/2-13)
- Handle with connecting rod to drive the part to exit the nut automatically
- New structure for easy operation and labor saving

No.	L(mm)			
90521	400	-	5	9

▲ Excluded from lifetime warranty terms.

90501 Manual Riveter 8"



- Nose piece configuration specifications including 24mm (3/32"); 3.2mm (1/8"); 4.0mm(5/32"); 4.8mm(3/16")
- Circular knurled nose piece available for removal without tools, nose piece with lock structure design, ensuring no looseness
- Ergonomic handle, comfortable and labor-saving

No.	Spec.			
90501	8"	-	10	6.1

▲ Excluded from lifetime warranty terms.

Heavy Duty Riveter



- Outer hexagon socket, available for operating stroke adjustment
- Thicker heat-treated handle, ensuring long service life
- 3-piece chromium-molybdenum alloy heat-treated claw, ensuring a long service life
- Nose piece replacement wrench fixed on the riveter, ensuring easy access

No.	Spec.			
90502	13"	-	8	9.5
90504	11"	10	10	16

▲ Excluded from lifetime warranty terms.