





UKF
Tapered bore (with adapter)
d₁ 20 ~ (50) mm



Variations of tolerance of distance from mounting surface to center of spherical bore (ΔA_{2s}) and tolerance of position of bolt hole (X)
Unit: mm

Housing No.		ΔA_{2s}	X
F205~F210	FX05~FX10	±0.5	0.7
F211~F218	FX11~FX20	±0.8	1

Variations of tolerance of bolt hole diameter (ΔN_s)
Unit: mm

Housing No.		ΔN_s
F205~F218	FX05~FX18	±0.2
	FX20	±0.3

Shaft Dia.		Dimensions									Bolt Size	Standard				Adapter Assembly No.	Mass	Basic		Fatigue	Factor	With Pressed Steel Cover				With Cast Iron Cover					
mm	inch	inch mm									inch mm	Unit No.	Housing No.	Bearing No.				Load Ratings kN	Load Limit kN			Unit No.		Dimension mm	Mass	Unit No.		Dimension mm	Mass		
d ₁		L	A	J	N	A ₁	A ₂	A ₀	B ₁	d _e (min.)												Open End Type	Closed End Type			mm	inch			kg	Open End Type
20	3/4	3 3/4 95	1 1/16 27	2 3/4 70	15/32 12	1/2 13	5/8 16	1 13/32 36	1 3/8 35	1 3/16 30	3/8 M10	UKF205	F205	UK205		HE2305X H2305X	0.87 0.87	14.0	7.85	0.357	13.9	— UKF205C	— UKF205D	— 40.5	— 1 19/32	— 0.87	— UKF205FC	— UKF205FD	— 49	— 1 15/16	— 1.1
	3/4	4 1/4 108	1 3/16 30	3 17/64 83	15/32 12	1/2 13	45/64 18	1 9/16 39.5	1 3/8 35	1 3/16 30	3/8 M10	UKFX05	FX05	UKX05		HE2305X H2305X	1.2 1.2	19.5	11.3	0.514	13.9	— UKFX05C	— UKFX05D	— 44.5	— 1 3/4	— 1.2	— —	— —	— —	— —	
	3/4	4 11/32 110	1 5/32 29	3 5/32 80	5/8 16	1/2 13	5/8 16	1 15/32 37.5	1 3/8 35	— —	1/2 M14	UKF305	F305	UK305		HE2305X H2305X	1.4 1.4	21.2	10.9	0.495	12.6	— —	— —	— —	— —	— —	— —	— —	— —	— —	
25	1	4 1/4 108	1 7/32 31	3 17/64 83	15/32 12	1/2 13	45/64 18	1 9/16 39.5	1 1/2 38	1 13/32 36	3/8 M10	UKF206	F206	UK206		H2306X HE2306X	1.3 1.3	19.5	11.3	0.514	13.9	UKF206C —	UKF206D —	44.5 —	1 3/4 —	1.3 —	UKF206FC —	UKF206FD —	53 —	2 3/32 —	1.6 —
	1	4 19/32 117	1 11/32 34	3 5/8 92	5/8 16	9/16 14	3/4 19	1 21/32 42	1 1/2 38	1 13/32 36	1/2 M14	UKFX06	FX06	UKX06		H2306X HE2306X	1.6 1.6	25.7	15.4	0.700	13.9	UKFX06C —	UKFX06D —	49 —	1 15/16 —	1.6 —	— —	— —	— —	— —	— —
	1	4 29/32 125	1 1/4 32	3 47/64 95	5/8 16	19/32 15	45/64 18	1 5/8 41	1 1/2 38	— —	1/2 M14	UKF306	F306	UK306		H2306X HE2306X	1.9 1.9	26.7	15.0	0.682	13.3	— —	— —	— —	— —	— —	— —	— —	— —	— —	— —
30	1 1/8	4 19/32 117	1 11/32 34	3 5/8 92	35/64 14	19/32 15	3/4 19	1 11/16 43	1 11/16 43	1 5/8 41	7/16 M12	UKF207	F207	UK207		HS2307X H2307X	1.6 1.6	25.7	15.4	0.700	13.9	— UKF207C	— UKF207D	— 49	— 1 15/16	— 1.6	— UKF207FC	— UKF207FD	— 58	— 2 9/32	— 2.0
	1 1/8	5 1/8 130	1 1/2 38	4 1/64 102	5/8 16	9/16 14	53/64 21	1 27/32 47	1 1/16 43	1 5/8 41	1/2 M14	UKFX07	FX07	UKX07		HS2307X H2307X	2.0 2.0	29.1	17.8	0.809	14.0	— UKFX07C	— UKFX07D	— 55.5	— 2 3/16	— 2.0	— —	— —	— —	— —	— —
	1 1/8	5 5/16 135	1 13/32 36	3 15/16 100	3/4 19	5/8 16	25/32 20	1 25/32 45.5	1 11/16 43	— —	5/8 M16	UKF307	F307	UK307		HS2307X H2307X	2.3 2.3	33.4	19.3	0.877	13.2	— —	— —	— —	— —	— —	— —	— —	— —	— —	— —
35	1 1/4 1 3/8	5 1/8 130	1 13/32 36	4 1/64 102	5/8 16	19/32 15	53/64 21	1 7/8 48	1 13/16 46	1 13/16 46	1/2 M14	UKF208	F208	UK208		HE2308X HS2308X H2308X	1.9 1.9 1.9	29.1	17.8	0.809	14.0	— — UKF208C	— — UKF208D	— — 55.5	— — 2 3/16	— — 1.9	— — UKF208FC	— — UKF208FD	— — 64	— — 2 17/32	— — 2.3
	1 1/4 1 3/8	5 13/32 137	1 9/16 40	4 9/64 105	3/4 19	9/16 14	55/64 22	1 31/32 50	1 13/16 46	1 13/16 46	5/8 M16	UKFX08	FX08	UKX08		HE2308X HS2308X H2308X	2.3 2.3 2.3	34.1	21.3	0.968	14.0	— — UKFX08C	— — UKFX08D	— — 56.5	— — 2 7/32	— — 2.3	— — —	— — —	— — —	— — —	— — —
	1 1/4 1 3/8	5 29/32 150	1 9/16 40	4 13/32 112	3/4 19	21/32 17	29/32 23	2 50.5	1 13/16 46	— —	5/8 M16	UKF308	F308	UK308		HE2308X HS2308X H2308X	3.1 3.1 3.1	40.7	24.0	1.09	13.2	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —
40	1 1/2	5 13/32 137	1 1/2 38	4 9/64 105	5/8 16	5/8 16	55/64 22	2 51	1 31/32 50	2 1/16 52	1/2 M14	UKF209	F209	UK209		HE2309X H2309X	2.3 2.3	34.1	21.3	0.968	14.0	— UKF209C	— UKF209D	— 56.5	— 2 7/32	— 2.3	— UKF209FC	— UKF209FD	— 66	— 2 19/32	— 2.8
	1 1/2	5 5/8 143	1 9/16 40	4 3/8 111	3/4 19	9/16 14	29/32 23	2 1/16 52	1 31/32 50	2 1/16 52	5/8 M16	UKFX09	FX09	UKX09		HE2309X H2309X	2.7 2.7	35.1	23.3	1.06	14.4	— UKFX09C	— UKFX09D	— 60	— 2 3/8	— 2.7	— —	— —	— —	— —	— —
	1 1/2	6 5/16 160	1 23/32 44	4 59/64 125	3/4 19	23/32 18	63/64 25	2 5/32 55	1 31/32 50	— —	5/8 M16	UKF309	F309	UK309		HE2309X H2309X	4.1 4.1	48.9	29.5	1.34	13.3	— —	— —	— —	— —	— —	— —	— —	— —	— —	— —
45	1 3/4	5 5/8 143	1 9/16 40	4 3/8 111	5/8 16	5/8 16	55/64 22	2 1/16 52	2 5/32 55	2 9/32 58	1/2 M14	UKF210	F210	UK210		HE2310X H2310X	2.6 2.6	35.1	23.3	1.06	14.4	— UKF210C	— UKF210D	— 59	— 2 5/16	— 2.6	— UKF210FC	— UKF210FD	— 70.5	— 2 25/32	— 3.1
	1 3/4	6 3/8 162	1 23/32 44	5 1/8 130	3/4 19	25/32 20	1 1/32 26	2 9/32 58	2 5/32 55	2 9/32 58	5/8 M16	UKFX10	FX10	UKX10		HE2310X H2310X	3.6 3.6	43.4	29.4	1.34	14.4	— UKFX10C	— UKFX10D	— 64	— 2 17/32	— 3.6	— —	— —	— —	— —	— —
	1 3/4	6 7/8 175	1 7/8 48	5 13/64 132	29/32 23	3/4 19	1 7/64 28	2 3/8 60	2 5/32 55	— —	3/4 M20	UKF310	F310	UK310		HE2310X H2310X	5.1 5.1	62.0	38.3	1.74	13.2	— —	— —	— —	— —	— —	— —	— —	— —	— —	— —
50	1 7/8	6 3/8 162	1 11/16 43	5 1/8 130	3/4 19	23/32 18	63/64 25	2 1/4 57.5	2 5/16 59	2 17/32 64	5/8 M16	UKF211	F211	UK211		HS2311X H2311X HE2311X	3.5 3.5 3.5	43.4	29.4	1.34	14.4	— UKF211C	— UKF211D	— 63	— 2 15/32	— 3.5	— UKF211FC	— UKF211FD	— 74.5	— 2 15/16	— 4.1
	2																														
	2	6 7/8 175	1 15/16 49	5 5/8 143	3/4 19	25/32 20	1 9/64 29	2 17/32 64.5	2 5/16 59	2 17/32 64	5/8 M16	UKFX11	FX11	UKX11		HS2311X H2311X HE2311X	4.6 4.6 4.6	52.4	36.2	1.65	14.4	— UKFX11C	— UKFX11D	— 73.5	— 2 29/32	— 4.6	— —	— —	— —	— —	— —

Remarks 1. In Part No. of unit and units with covers, fitting codes follow bore diameter numbers. (See Table 2.5 in P.11.)

2. Part No. of applicable grease nipples are shown below.

A-1/4-28UNF 205~210, X05~X09, 305~308

A-R1/8 211~218, X10~X20, 309~328

3. In Part No. of unit with adapters and bearing with adapters, Part No. of applicable adapter follow the Part No. shown in the dimensional tables.

(Example of Part No. : UKF206J + H2306X, UK206 + H2306X)





4. As for the triple-lip seal type product (205 is the double-lip seal type product), supplementary code L3 (L2) follows the Part No. of unit or bearing.

(Example of Part No. : UKF206JL3 + H2306X, UK206L3 + H2306X)

5. For the dimensions and forms of applicable bearings and adapters, see the dimensional tables of insert bearing for unit and adapter assemblies.

6. Housings of spheroidal graphite iron casting are also available.

UKF
Tapered bore (with adapter)
d₁ (50) ~ (90) mm



Variations of tolerance of distance from mounting surface to center of spherical bore (ΔA_{2s}) and tolerance of position of bolt hole (X)

Housing No.			ΔA_{2s}	X
F205~F210	FX05~FX10	F305~F310	± 0.5	0.7
F211~F218	FX11~FX20	F311~F328	± 0.8	1



Variations of tolerance of bolt hole diameter (ΔN_s)

Housing No.			ΔN_s
F205~F218	FX05~FX18	F305~F315	± 0.2
	FX20	F316~F328	± 0.3

Shaft Dia. mm inch		Dimensions inch mm									Bolt Size inch mm	Standard				Adapter Assembly No.	Mass kg	Basic Load Ratings kN		Fatigue Load Limit kN	Factor <i>f</i> ₀	With Pressed Steel Cover				With Cast Iron Cover			
		<i>L</i>	<i>A</i>	<i>J</i>	<i>N</i>	<i>A</i> ₁	<i>A</i> ₂	<i>A</i> ₀	<i>B</i> ₁	<i>d</i> _e (min.)		Unit No.	Housing No.	Bearing No.				<i>C</i> _r	<i>C</i> _{0r}			<i>C</i> _u	Unit No. Open End Type	Unit No. Closed End Type	Dimension mm inch <i>A</i> _s	Mass kg	Unit No. Open End Type	Unit No. Closed End Type	Dimension mm inch <i>A</i> _c
50	1 7/8	7 9/32 185	2 1/16 52	5 33/64 140	29/32 23	25/32 20	1 3/16 30	2 17/32 64	2 5/16 59	— —	3/4 M20	UKF311	F311	UK311		HS2311X H2311X HE2311X	5.9 5.9 5.9	71.6 45.0	2.05	13.2	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —	
	2	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —					— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —
55	2 1/8	6 7/8 175	1 7/8 48	5 5/8 143	3/4 19	23/32 18	1 9/64 29	2 19/32 65.5	2 7/16 62	2 23/32 69	5/8 M16	UKF212	F212	UK212		HS2312X H2312X	4.1 4.1	52.4 36.2	1.65	14.4	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —	
	2 1/8	7 3/8 187	2 5/16 59	5 55/64 149	3/4 19	13/16 21	1 11/32 34	2 9/16 65	2 7/16 62	2 23/32 69	5/8 M16					UKFX12	FX12	UKX12		HS2312X H2312X	5.5 5.5	57.2 40.1	1.82	14.4	UKF212C UKFX12C	UKF212D UKFX12D	73.5 2 29/32 78.5 3 3/32	4.1 5.5	UKF212FC —
	2 1/8	7 11/16 195	2 7/32 56	5 29/32 150	29/32 23	7/8 22	1 19/64 33	2 3/4 69.5	2 7/16 62	— —	3/4 M20	UKF312	F312	UK312		HS2312X H2312X	6.8 6.8	81.9 52.2	2.37	13.2	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —	
	2 1/8	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —					— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —
60	2 1/4	7 3/8 187	1 31/32 50	5 55/64 149	3/4 19	7/8 22	1 3/16 30	2 21/32 67.5	2 9/16 65	2 29/32 74	5/8 M16	UKF213	F213	UK213		HE2313X H2313X	5.1 5.1	57.2 40.1	1.82	14.4	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —	
	2 3/8	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —					— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —
	2 1/4	7 3/8 187	2 5/16 59	5 55/64 149	3/4 19	13/16 21	1 11/32 34	2 11/16 68	2 9/16 65	2 29/32 74	5/8 M16	UKFX13	FX13	UKX13		HE2313X H2313X	6.0 6.0	62.2 44.1	2.01	14.5	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —	
	2 3/8	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —					— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —
	2 1/4	8 3/16 208	2 9/32 58	6 17/32 166	29/32 23	7/8 22	1 19/64 33	2 13/16 71.5	2 9/16 65	— —	3/4 M20	UKF313	F313	UK313		HE2313X H2313X	7.9 7.9	92.7 59.9	2.68	13.2	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —	
	2 3/8	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —					— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —
65	2 1/2	7 7/8 200	2 7/32 56	6 17/64 159	3/4 19	7/8 22	1 11/32 34	2 15/16 74.5	2 7/8 73	3 11/32 85	5/8 M16	UKF215	F215	UK215		HE2315X H2315X	6.5 6.5	67.4 48.3	2.17	14.5	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —	
	2 1/2	7 3/4 197	2 11/16 68	5 53/64 152	29/32 23	15/16 24	1 9/16 40	3 76	2 7/8 73	3 11/32 85	3/4 M20					UKFX15	FX15	UKX15		HE2315X H2315X	8.1 8.1	72.7 53.0	2.30	14.6	UKF215C UKFX15C	UKF215D UKFX15D	83.5 3 9/32 94.5 3 23/32	6.5 8.1	UKF215FC —
	2 1/2	9 9/32 236	2 19/32 66	7 1/4 184	63/64 25	31/32 25	1 17/32 39	3 7/32 81.5	2 7/8 73	— —	7/8 M22	UKF315	F315	UK315		HE2315X H2315X	11.7 11.7	113 77.2	3.24	13.2	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —	
2 3/4	8 3/16 208	2 9/32 58	6 1/2 165	29/32 23	7/8 22	1 11/32 34	3 3/32 78.5	3 1/16 78	3 17/32 90	3/4 M20	UKF216					F216	UK216		HE2316X H2316X	7.6 7.6	72.7 53.0	2.30	14.6	— — —	— — —	— — —	— — —	— — —	— — —
70	2 3/4	8 7/16 214	2 3/4 70	6 47/64 171	29/32 23	15/16 24	1 9/16 40	3 1/8 79	3 1/16 78	3 17/32 90	3/4 M20	UKFX16	FX16	UKX16		HE2316X H2316X	9.5 9.5	84.0 61.9	2.60	14.5	— — —	— — —	— — —	— — —	— — —	— — —	— — —		
	2 3/4	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —					— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —
	2 3/4	9 27/32 250	2 11/16 68	7 23/32 196	1 7/32 31	1 1/16 27	1 1/2 38	3 1/4 82.5	3 1/16 78	— —	1 M27	UKF316	F316	UK316		HE2316X H2316X	12.9 12.9	123 86.7	3.53	13.3	— — —	— — —	— — —	— — —	— — —	— — —	— — —		
75	—	8 21/32 220	2 15/32 63	6 57/64 175	29/32 23	15/16 24	1 13/32 36	3 1/4 82.5	3 7/32 82	3 25/32 96	3/4 M20	UKF217	F217	UK217		H2317X HE2317X	9.0 9.0	84.0 61.9	2.60	14.5	— — —	— — —	— — —	— — —	— — —	— — —	— — —		
	3	8 7/16 214	2 3/4 70	6 47/64 171	29/32 23	15/16 24	1 9/16 40	3 7/32 82	3 7/32 82	3 25/32 96	3/4 M20					UKFX17	FX17	UKX17		H2317X HE2317X	10.4 10.4	96.1 71.5	2.91	14.5	UKF217C —	UKF217D —	92.5 3 21/32 101.5 4	9.0 10.4	UKF217FC —
	3	10 1/4 260	2 29/32 74	8 1/32 204	1 7/32 31	1 1/16 27	1 47/64 44	3 5/8 92	3 7/32 82	— —	1 M27	UKF317	F317	UK317		H2317X HE2317X	15.2 15.2	133 96.8	3.82	13.3	— — —	— — —	— — —	— — —	— — —	— — —	— — —		
	3	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —					— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —	— — —
80	—	9 1/4 235	2 11/16 68	7 23/64 187	29/32 23	31/32 25	1 9/16 40	3 17/32 89.5	3 3/8 86	4 1/32 102	3/4 M20	UKF218	F218	UK218		H2318X	11.4	96.1 71.5	2.91	14.5	— — —	— — —	— — —	— — —	— — —	— — —	— — —		
	—	8 7/16 214	3 76	6 47/64 171	29/32 23	15/16 24	1 49/64 45	3 15/32 88	3 3/8 86	4 1/32 102	3/4 M20					UKFX18	FX18	UKX18		H2318X	11.4	109 81.9	3.23	14.4	UKF218C —	UKF218D —	101.5 4 —	11.4 —	UKF218FC —
	—	11 1/32 280	3 76	8 1/2 216	1 3/8 35	1 3/16 30	1 47/64 44	3 5/8 92	3 3/8 86	— —	1 1/8 M30	UKF318	F318	UK318		H2318X	19.0	143 107	4.11	13.3	— — —	— — —	— — —	— — —	— — —	— — —	— — —		
85	3 1/4	11 13/32 290	3 11/16 94	8 31/32 228	1 3/8 35	1 3/16 30	2 21/64 59	4 3/8 111	3 17/32 90	— —	1 1/8 M30	UKF319	F319	UK319		HE2319X H2319X	21.9 21.9	153 119	4.45	13.3	— — —	— — —	— — —	— — —	— — —	— — —	— — —		
90	3 1/2	10 9/16 268	3 13/16 97	8 5/16 211	1 7/32 31	1 3/32 28	2 21/64 59	4 3/16 106	3 13/16 97	4 13/32 112	1 M27					UKFX20	FX20	UKX20		HE2320X H2320X	18.4 18.4	133 105	3.91	14.4	— — —	— — 			

Remarks 1. In Part No. of unit and units with covers, fitting codes follow bore diameter numbers. (See Table 2.5 in P.11.)
2. Part No. of applicable grease nipples are shown below.
A-1/4-28UNF 205~210, X05~X09, 305~308
A-R1/8 211~218, X10~X20, 309~328
3. In Part No. of unit with adapters and bearing with adapters, Part No. of applicable adapter follow the Part No. shown in the dimensional tables.
(Example of Part No. : UKF206J + H2306X, UK206 + H2306X)
4. As for the triple-lip seal type product (205 is the double-lip seal type product), supplementary code L3 (L2) follows the Part No. of unit or bearing.
(Example of Part No. : UKF206JL3 + H2306X, UK206L3 + H2306X)
5. For the dimensions and forms of applicable bearings and adapters, see the dimensional tables of insert bearing for unit and adapter assemblies.
6. Housings of spheroidal graphite iron casting are also available.

UKF
Tapered bore (with adapter)
 d_1 (90) ~ 125 mm



Variations of tolerance of distance from mounting surface to center of spherical bore ($\angle_{A2s}$) and tolerance of position of bolt hole (X)

Housing No.			$\angle_{A2s}$	X
F205~F210	FX05~FX10	F305~F310	± 0.5	0.7
F211~F218	FX11~FX20	F311~F328	± 0.8	1

Unit: mm

Variations of tolerance of bolt hole diameter ($\angle_{Ns}$)

Housing No.			$\angle_{Ns}$
F205~F218	FX05~FX18	F305~F315	± 0.2
	FX20	F316~F328	± 0.3

Unit: mm

Shaft Dia. mm inch		Dimensions									Bolt Size inch mm	Standard				Adapter Assembly No.	Mass kg	Basic		Fatigue Load Limit kN	Factor	With Pressed Steel Cover				With Cast Iron Cover			
		inch mm										Unit No.	Housing No.	Bearing No.				Load Ratings kN				Dimension mm inch	Mass kg	Unit No.		Dimension mm inch	Mass kg		
		<i>L</i>	<i>A</i>	<i>J</i>	<i>N</i>	<i>A</i> ₁	<i>A</i> ₂	<i>A</i> ₀	<i>B</i> ₁	<i>d</i> _e (min.)								Open End Type	Closed End Type					<i>A</i> _s	kg			Open End Type	Closed End Type
90	3 1/2	12 7/32	3 11/16	9 17/32	1 1/2	1 1/4	2 21/64	4 7/16	3 13/16	—	1 1/4	UKF320	F320	UK320		HE2320X	25.4						—	—	—	—	—	—	—
		310	94	242	38	32	59	113	97	—	M33						H2320X	25.4	173	141	5.08	13.2	—	—	—	—	—	—	UKF320C
100	4	13 3/8	3 25/32	10 15/32	1 39/64	1 3/8	2 23/64	4 23/32	4 1/8	—	1 3/8	UKF322	F322	UK322		H2322X	35.2						—	—	—	—	—	—	—
		340	96	266	41	35	60	120	105	—	M36						HE2322X	35.2	205	180	6.15	13.2	—	—	—	—	—	—	—
110	—	14 9/16	4 11/32	11 27/64	1 39/64	1 9/16	2 9/16	5 1/8	4 13/32	—	1 3/8	UKF324	F324	UK324		H2324	47.6						—	—	—	—	—	—	—
		370	110	290	41	40	65	130.5	112	—	M36							207	185	6.10	13.5	—	—	—	—	—	—	—	—
115	4 1/2	16 5/32	4 17/32	12 19/32	1 39/64	1 25/32	2 9/16	5 3/16	4 3/4	—	1 3/8	UKF326	F326	UK326		HE2326	65.3						—	—	—	—	—	—	—
		410	115	320	41	45	65	131.5	121	—	M36						H2326	65.3	229	214	6.79	13.6	—	—	—	—	—	—	—
125	—	17 23/32	4 29/32	13 25/32	1 39/64	2 5/32	2 61/64	5 13/16	5 5/32	—	1 3/8	UKF328	F328	UK328		H2328	74.9						—	—	—	—	—	—	—
		450	125	350	41	55	75	147.5	131	—	M36							253	246	7.54	13.6	—	—	—	—	—	—	—	—

Remarks 1. In Part No. of unit and units with covers, fitting codes follow bore diameter numbers. (See Table 2.5 in P.11.)

2. Part No. of applicable grease nipples are shown below.

A-1/4-28UNF..... 205~210, X05~X09, 305~308

A-R1/8..... 211~218, X10~X20, 309~328

3. In Part No. of unit with adapters and bearing with adapters, Part No. of applicable adapter follow the Part No. shown in the dimensional tables.

(Example of Part No. : UKF206J + H2306X, UK206 + H2306X)

4. As for the triple-lip seal type product (205 is the double-lip seal type product), supplementary code L3 (L2) follows the Part No. of unit or bearing.

(Example of Part No. : UKF206JL3 + H2306X, UK206L3 + H2306X)

5. For the dimensions and forms of applicable bearings and adapters, see the dimensional tables of insert bearing for unit and adapter assemblies.

6. Housings of spheroidal graphite iron casting are also available.