



Classical V-belts

All sizes of Mitsubishi V-belts respectively meet the dimensional requirements as stated in DIN 2215/ISO 4184 shown below.

Table 1-2

B/17, BX



B-Section

Belt Code	Inner length Li (mm)	Datum length Ld (mm)	Belt Code	Inner length Li (mm)	Datum length Ld (mm)
25	630	673	75	1900	1943
26	660	703	76	1930	1973
27	686	729	77	1950	1993
28	710	753	78	1981	2024
29	735	778	79	2000	2043
30	762	805	80	2032	2075
31	785	828	81	2060	2103
32	813	856	82	2083	2126
33	838	881	83	2100	2143
34	865	908	84	2134	2177
35	889	932	85	2160	2203
36	915	958	86	2200	2243
37	940	983	87	2210	2253
38	965	1008	88	2240	2283
39	991	1034	89	2260	2303
40	1016	1059	90	2286	2329
41	1040	1083	91	2300	2343
42	1060	1103	92	2337	2380
43	1090	1133	93	2360	2403
44	1120	1163	94	2388	2431
45	1150	1193	95	2413	2456
46	1175	1218	96	2438	2481
47	1200	1243	97	2465	2508
48	1215	1258	98	2500	2543
49	1250	1293	99	2515	2558
50	1275	1318	100	2540	2583
51	1300	1343	102	2600	2643
52	1320	1363	105	2667	2710
53	1350	1393	106	2700	2743
54	1372	1415	108	2750	2793
55	1400	1443	110	2800	2843
56	1425	1468	112	2845	2888
57	1450	1493	115	2921	2964
58	1475	1518	118	3000	3043
59	1500	1543	120	3048	3091
60	1525	1568	122	3099	3142
61	1550	1593	125	3175	3218
62	1575	1618	128	3250	3293
63	1600	1643	130	3300	3343
64	1625	1668	132	3350	3393
65	1650	1693	135	3425	3468
66	1675	1718	138	3500	3543
67	1700	1743	140	3550	3593
68	1725	1768	145	3675	3718
69	1750	1793	150	3810	3853
70	1775	1818	155	3937	3980
71	1800	1843	160	4065	4108
72	1825	1868	Size range: 23" ~ 660"		
73	1850	1893			
74	1880	1923			

: Available size for Raw Edge Cogged V-belts BX




Classical V-belts

All sizes of Mitsubishi V-belts respectively meet the dimensional requirements as stated in DIN 2215/ISO 4184 shown below.

Table 1-3

C/22, CX



Belt indication

C 93
 | |
 Cross Section Belt Code(inch)

C-Section

Belt Code	Inner length Li (mm)	Datum length Ld (mm)	Belt Code	Inner length Li (mm)	Datum length Ld (mm)
40	1000	1052	96	2438	2490
42	1075	1127	97	2465	2517
45	1150	1202	98	2500	2552
48	1220	1272	99	2525	2577
50	1270	1322	100	2540	2592
51	1295	1347	102	2591	2643
52	1320	1372	105	2667	2719
53	1350	1402	108	2750	2802
54	1375	1427	110	2800	2852
55	1400	1452	112	2845	2897
56	1425	1477	115	2921	2973
57	1450	1502	118	3000	3052
58	1475	1527	120	3050	3102
59	1500	1552	122	3100	3152
60	1525	1577	125	3175	3227
61	1550	1602	128	3250	3302
62	1575	1627	130	3300	3352
63	1600	1652	132	3350	3402
64	1625	1677	138	3500	3552
65	1650	1702	140	3550	3602
66	1675	1727	142	3600	3652
67	1700	1752	148	3750	3802
68	1725	1777	150	3810	3862
69	1750	1802	155	3937	3989
70	1775	1827	160	4064	4116
71	1800	1852	170	4318	4370
72	1829	1881	180	4572	4624
73	1854	1906	190	4825	4877
74	1880	1932	195	4950	5002
75	1900	1952	197	5000	5052
76	1930	1982	200	5080	5132
77	1956	2008	210	5334	5386
78	1981	2033	220	5600	5652
79	2000	2052	230	5842	5894
80	2032	2084	240	6096	6148
81	2060	2112	250	6350	6402
82	2083	2135	260	6600	6652
83	2108	2160	270	6858	6910
84	2135	2187	Size range: 37" ~ 660"		
85	2159	2211			
86	2184	2236			
87	2210	2262			
88	2240	2292			
89	2261	2313			
90	2286	2338			
91	2311	2363			
92	2337	2389			
93	2360	2412			
94	2388	2440			
95	2413	2465			

Available size for Raw Edge Cogged V-belts CX

1

Properties

