


VINYL-INSULATED SPADE TERMINALS

MAXIMUM ELECTRIC CURRENT:

A.W.G.	22	20	18	16	14
AMP.	9	12	17	18	30

MAXIMUM ELECTRICAL RATING: 105°C 600 VOLTS MAX.
INSULATION MATERIAL: VINYL
INSULATION COLOR:

 22-16 A.W.G.: RED ■ 16-14 A.W.G.: BLUE ■
TERMINAL MATERIAL: COPPER


WIRE RANGE A.W.G. mm ²	ITEM NO.		STUD SIZE		DIMENSION inch mm							CRIMPING TOOL	Q'TY BOX
	BRAZED SEAM	BUTTED SEAM	d2		W	F	L	E	D	d1	T		
22-16 A.W.G. 0.5-1.5 mm ²	SVB1-3.2	SV1-3.2 *	#4	.126 3.2	.224 5.7							IZUMI MODEL 34 WITH DIE INDEX COLOR:RED OR K.S. MODEL KST2000A HRI-126J WITH DIE INDEX COLOR:RED	1000
	SVBS1-3.7	SVS1-3.7 *	#6	.146 3.7									1000
	SVBL1-3.7	SVL1-3.7 *	#6	.146 3.7									1000
	SVBLL1-3.7	SVLL1-3.7 *	#6	.146 3.7									1000
	SVBS1-4	SVS1-4 *	#8	.169 4.3									1000
	SVBM1-4	SVM1-4 *	#8	.169 4.3									1000
	SVBL1-4	SVL1-4 *	#8	.169 4.3									1000
	SVBS1-5	SVS1-5 *	#10	.209 5.3									1000
	SVBL1-5	SVL1-5 *	#10	.209 5.3									1000
	SVBS1-6	SVS1-6 *	1/4	.252 6.4									1000
16-14 A.W.G. 1.5-2.5 mm ²	SVB2-3.2	SV2-3.2 *	#4	.126 3.2	.256 6.5	.827 21.0	.394 10.0	.157 4.0		.067 1.7	.030 0.75	IZUMI MODEL 34 WITH DIE INDEX COLOR:BLUE OR K.S. MODEL KST2000A HRI-126J WITH DIE INDEX COLOR:BLUE	1000
	SVBS2-3.7	SVS2-3.7 *	#6	.146 3.7									1000
	SVBL2-3.7	SVL2-3.7 *	#6	.146 3.7									1000
	SVBLL2-3.7	SVLL2-3.7 *	#6	.146 3.7									1000
	SVBS2-4	SVS2-4 *	#8	.169 4.3									1000
	SVBM2-4	SVM2-4 *	#8	.169 4.3									1000
	SVBL2-4	SVL2-4 *	#8	.169 4.3									1000
	SVBS2-5	SVS2-5 *	#10	.209 5.3									1000
	SVBL2-5	SVL2-5 *	#10	.209 5.3									1000
	SVBS2-6	SVS2-6 *	1/4	.252 6.4									1000
16-14 A.W.G. 1.5-2.5 mm ²	SVB2-3.2	SV2-3.2 *	#4	.126 3.2	.433 11.0	1.063 27.0							1000
	SVBS2-3.7	SVS2-3.7 *	#6	.146 3.7									1000
	SVBL2-3.7	SVL2-3.7 *	#6	.146 3.7									1000
	SVBLL2-3.7	SVLL2-3.7 *	#6	.146 3.7									1000
	SVBS2-4	SVS2-4 *	#8	.169 4.3									1000
	SVBM2-4	SVM2-4 *	#8	.169 4.3									1000
	SVBL2-4	SVL2-4 *	#8	.169 4.3									1000
	SVBS2-5	SVS2-5 *	#10	.209 5.3									1000
	SVBL2-5	SVL2-5 *	#10	.209 5.3									1000
	SVBS2-6	SVS2-6 *	1/4	.252 6.4									1000
16-14 A.W.G. 1.5-2.5 mm ²	SVB2-3.2	SV2-3.2 *	#4	.126 3.2	.472 12.0								1000
	SVBS2-3.7	SVS2-3.7 *	#6	.146 3.7									1000
	SVBL2-3.7	SVL2-3.7 *	#6	.146 3.7									1000
	SVBLL2-3.7	SVLL2-3.7 *	#6	.146 3.7									1000
	SVBS2-4	SVS2-4 *	#8	.169 4.3									1000
	SVBM2-4	SVM2-4 *	#8	.169 4.3									1000
	SVBL2-4	SVL2-4 *	#8	.169 4.3									1000
	SVBS2-5	SVS2-5 *	#10	.209 5.3									1000
	SVBL2-5	SVL2-5 *	#10	.209 5.3									1000
	SVBS2-6	SVS2-6 *	1/4	.252 6.4									1000
16-14 A.W.G. 1.5-2.5 mm ²	SVB2-3.2	SV2-3.2 *	#4	.126 3.2	.472 12.0								1000
	SVBS2-3.7	SVS2-3.7 *	#6	.146 3.7									1000
	SVBL2-3.7	SVL2-3.7 *	#6	.146 3.7									1000
	SVBLL2-3.7	SVLL2-3.7 *	#6	.146 3.7									1000
	SVBS2-4	SVS2-4 *	#8	.169 4.3									1000
	SVBM2-4	SVM2-4 *	#8	.169 4.3									1000
	SVBL2-4	SVL2-4 *	#8	.169 4.3									1000
	SVBS2-5	SVS2-5 *	#10	.209 5.3									1000
	SVBL2-5	SVL2-5 *	#10	.209 5.3									1000
	SVBS2-6	SVS2-6 *	1/4	.252 6.4									1000



ALL LISTED

*: ADDITIONAL CERTIFIED