



FAG




NU202-E-XL-TVP2

Cylindrical roller bearing

Cylindrical roller bearing NU..-E-XL-TVP2, with cage, single row, non-locating bearing, 2 ribs on outer ring, 0 ribs on inner ring (smooth), type NU, Running accuracy in P6

X-life

Thông số kĩ thuật



Mẫu mã sản phẩm hiện tại của bạn

Design	E	Increased Capacity Design
Cage	TVP2	Solid Window Cage made from PA66
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (PN)
Number of rolling element rows	1	Single-row design

Main Dimensions & Performance Data

d	15 mm	Bore diameter
D	35 mm	Outside diameter
B	11 mm	Width
C _r	15,100 N	Basic dynamic load rating, radial
C _{0r}	10,400 N	Basic static load rating, radial
C _{ur}	1,440 N	Fatigue load limit, radial
n _G	31,000 1/min	Limiting speed
n _{gr}	17,900 1/min	Reference speed
≈m	0.047 kg	Trọng lượng



Mounting dimensions

$d_{a \min}$	17.4 mm	Minimum diameter shaft shoulder
$d_{a \max}$	18.5 mm	Maximum diameter of shaft shoulder
$d_{b \min}$	20 mm	Minimum shaft shoulder
$D_{a \max}$	32.6 mm	Maximum diameter of housing shoulder
$r_{a \max}$	0.6 mm	Maximum recess radius
$r_{a1 \max}$	0.3 mm	Maximum recess radius

Dimensions

$r_{\min}$	0.6 mm	Minimum chamfer dimension
$r_{1 \min}$	0.3 mm	Minimum chamfer dimension
s	1.6 mm	Axial displacement
E	30.3 mm	Raceway diameter outer ring
F	19.3 mm	Raceway diameter inner ring
$D_{1 \min}$	28 mm	Minimum rib diameter outer ring

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

Đặc tính

	Tải hướng kính
	Bôi trơn bằng mỡ
	Bôi trơn bằng dầu
	Không phốt