

Air Tool

Professional Pistol Grip Air Screwdriver



02311A

- Small size for flexible operation
- One switch of forward and reverse for one-handed operation
- Dual hammer strike structure provides stable torque output



02312A

- Self-resetting blade design for fast and powerful start-up
- One switch of forward and reverse for one-handed operation
- Dual hammer strike structure provides stable torque output

Professional Straight Grip Air Screwdriver



02313A



02314A



02315A

- High precise cylinder ensures durability
- Forward and reverse adjustable in 3 level

No.	Output End Specification	Working Torque ² (N-m)	Max. Reversal Torque ⁵ (N-m)	Free Speed (RPM)	Bolt Tightening Capacity ¹	Average Gas Consumption (CFM)	Noise Level ² dB(A)	L×W×H(mm)	Air Inlet Size	Min. Air Hose ID(mm)	Working Air Pressure ³ (Kgf/cm ²)	Unit Weight (kg)			
02311A	1/4" hex	50	68	11000	M6	3.5	90	146x167x41	1/4"	8	6.35	0.88	1	10	8.9
02312A	1/4" hex	100	120	9000	M12	4.2	98	161x171x46	1/4"	8	6.35	1.15	1	10	11
02313A	1/4" hex	50	68	11000	M6	3.5	100	175x62x41	1/4"	8	6.35	0.73	1	16	11.4
02314A	1/4" hex	40	68	11000	M6	3.5	100	175x62x41	1/4"	8	6.35	0.73	1	16	11.4
02315A	1/4" hex	90	110	7000	M8	3.5	95	185x63x47	1/4"	8	6.35	0.99	1	16	15.5

¹ For tightening capability standard for bolts, refer to bolts with strength level of 12.9 in DIN 267. ² Noise level is sound pressure of level A. ³ Working air pressure refers to the real-time dynamic air pressure measured at the air inlet of the product during idling operation; ⁴ Working torque refers to the accumulated torque actually output by the tool running forward for 5 seconds under working pressure; ⁵ Maximum reversing torque refers to the torque actually accumulated when the tool reverses for 15 seconds under operating air pressure