

## Led-free Coiled Soldering Wire



- Led under 0.02% for environment protection and friendly smell
- Even flux distribution for high welding efficiency
- RoHS certified

| No.   | Spec.      |  |  |  |
|-------|------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|
| 90321 | 0.5MM/250g | 1                                                                                 | 10                                                                                | 2.6                                                                               |
| 90322 | 0.8MM/250g | 1                                                                                 | 10                                                                                | 2.6                                                                               |
| 90323 | 1.0MM/250g | 1                                                                                 | 10                                                                                | 2.6                                                                               |
| 90324 | 1.0MM/250g | 1                                                                                 | 10                                                                                | 5.2                                                                               |

▲ Excluded from lifetime warranty terms.

## 90315 Pocket Pack Soldering Wire 1.0mm/17g



- Meeting national standards and the requirements of federal regulations of the United States
- Made of highly-purified lead tin alloy
- Made from 63% tin and 2% flux and suitable for printed circuit boards with strict temperature limits and other places with limited narrow melting temperature range of lead
- Few solder residues produced, and solder joints, being clean, plump and bright with low corrosivity
- Small smoke and irritation produced, ensuring safe operation of operators for fast melting, fast welding speed, and improved work efficiency

| No.   |  |  |  |
|-------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| 90315 | -                                                                                   | 24                                                                                  | 0.7                                                                                 |

▲ Excluded from lifetime warranty terms.

## 03511 Plastic Desoldering Pump



- Strong suction, able to realize fast and effective removal of soldering tin, and rapid separation of connectors
- High quality PTFE suction nozzle, featuring high resistance to high temperature and solvent

| No.   |  |  |  |
|-------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| 03511 | 12                                                                                  | 48                                                                                  | 4.1                                                                                 |

▲ Excluded from lifetime warranty terms.

## 03512 Aluminum Desoldering Pump



- Strong suction, able to realize fast and effective removal of soldering tin, and rapid separation of connectors
- High quality PTFE suction nozzle, featuring high resistance to high temperature and solvent

| No.   |  |  |  |
|-------|-----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| 03512 | 12                                                                                | 48                                                                                  | 4.3                                                                                 |

▲ Excluded from lifetime warranty terms.

## 03513 5Pc. Desoldering Pump Tips



- High quality PTFE suction nozzle, featuring high resistance to high temperature and solvent

| No.   |  |  |  |
|-------|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| 03513 | 25                                                                                  | -                                                                                     | -                                                                                     |

▲ Excluded from lifetime warranty terms.

## 03080 Multi-functional Pen Multimeter



- Automatic range and full-scale overload protection
- Black crystal high-brightness large screen with maximum reading 5999
- Used to measure AC/DC, frequency, capacitance, resistance, diode and continuity
- Room temperature monitoring

| No.   |  |  |  |
|-------|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| 03080 | 1                                                                                   | 18                                                                                    | -                                                                                     |

▲ Warranty of 2 years (excluding fuse, battery and probe).