

## 97204A Quick Release Grease Gun 600cc



- Engineering machine
- Agriculture equipments
- Automobiles
- For #0-#3 grease only
- New "flared" exhaust nozzle design ensures better exhaust effect and reduces empty bleeding
- Add an anti-impurity filter screen to prevent impurities from entering the grease pipeline and causing block-age during filling of bulk grease
- Lightweight aluminum tip and extended handle design makes the product more labor-saving and more portable
- Equipped with grease gun hose and tip nozzle to meet the grease filling requirements of small space or multiple nozzles

No.	Working pressure (PSI)	Burst pressure (PSI)	Oil pump capacity			
97204A	7000	10000	1.20z/40 compressions (36cc/40 compressions)	-	10	18

▲ Excluded from lifetime warranty terms.

## 97205 High Pressure Grease Gun 400cc



- High-low pressure switch, easy to operate
- Patented circulating air bleed valve, ensuring to discharge air in the gun cylinder, making the grease gun operate smootherly
- Patented large-small shaft design, lubricating through switching from high pressure to low pressure and vice versa. Firstly use high pressure to get through the grease passage instantly, to ensure smooth filling of grease; then switch to low pressure to fill in grease rapidly, thus increasing working efficiency
- Unique square thread, ensuring convenient assembly and disassembly of the nozzle and the gun cylinder, increasing airtightness
- Detachable rear cover for easy cleaning of the gun cylinder
- Heavy duty thickened handle, bearing higher operating forces

No.	Working pressure (PSI)	Burst pressure (PSI)	Oil pump capacity			
97205	Small core: 8000 Large core: 1000	Small core: 13000 Large core: 2000	Small core: 0.50Z/40 compressions Large core: 3.50Z/40 compressions	-	10	22.9

▲ Excluded from lifetime warranty terms.

## 97206 Transparent Barrel Grease Gun 400cc




- Engineering machine
- Agriculture equipments
- Automobiles
- Aluminum alloy adapter, enable frequent open and close the nozzle to fill in grease, avoid direct connection between the cylinder and nozzle to increase durability
- Special transparent tube design, easy to observe the reserved grease amount
- Self-locking rear cover is easy to be removed

No.	Working pressure (PSI)	Burst pressure (PSI)	Oil pump capacity			
97206	4500	7000	1 OZ/40 compressions	-	12	22.9

▲ Excluded from lifetime warranty terms.

## 97101 Tire Valve Extractor 320mm



- For quick removing or installation of tire valve inserts

No.	L(mm)			
97101	320	12	60	19

## 97211 Grease Gun Coupler



- Nozzle with special design added a steel ball, preventing the grease from returning

No.			
97211	18	72	3.3

▲ Excluded from lifetime warranty terms.