

62603 Multi-functional Digital Circuit Tester



- Multi-functional as circuit tester and tightening with exchangeable Slotted and Phillips bits head
- Rechargeable through Type-C output
- Available for detection of AC and DC voltage, and segmented LCD. Test range: 12-250AC/DC
- Available for checking on/off states of circuits, distinguishing zero wire and phase wire, finding break-point
- With non-contact induction test function, available for detecting automobile high voltage branch wires
- With LED lighting, torch functional and facilitating test in a dark environment

▲ Warning

Before conducting test, first do self-inspection for the test pen, and test a known circuit with the inspected pen. If the test fails, please replace the battery. If the pen still does not work, please contact the dealer

No.	Test Range	L×W×H(mm)			
62603	12-250V	145×23×20	15	60	2.7

▲ Excluded from lifetime warranty terms.

62702A High-precision Non-contact Test Probe



AC voltage test range	About 12V-1000V [The "S" function button indicator is on] 50Hz/60Hz
Frequency	✓
Auto power-off	✓
Battery under-voltage warning	✓
Operating temperature	0oC~40oC
Battery	2x1.5V AAA battery
Size	162X23X27mm
Weight	About 48g

- Safety level CAT III 1000V
- Three voltage signal intensity indicators
- LED for operation in dark environment
- Prompt mode: sound and light prompt

No.			
62702A	15	60	6.3

▲ Exclude from lifetime warranty terms.

Ratcheting Cable Cutter



- Used for cutting copper and aluminum cables and armoured cables
- Not used for stranded steel wires, stranded steel-conductor aluminium wires and steel wire ropes
- Two-stage driver for labor-saving cutting
- Special linkage type feeding mechanism allows for faster feeding and higher cutting efficiency
- Lightweight, compact structure, easy to carry

No.	Spec.	L(mm)	Max. Cutting Diameter (mm)			
72511	240mm ²	245	36	3	6	4.9
72512	400mm ²	320	52	3	6	6.6

▲ Excluded from lifetime warranty terms.

03109 Electricians Knife, Straight Blade 70mm



◀ After folding

- It is made of special hard steel containing manganese and thus boasts good toughness
- The blade hardness is greater than 52HRC (Rockwell hardness), achieving high durability and strong cutting power
- The handle is made of imported rosewood, achieving aesthetic appearance and comfortable operation

Note

- Please keep the blade clean and dry after operation.
- Keep blade away from saline environments to prevent rusting
- Please preserve the product with antirust paint before putting it into a long-term stoppage
- This product is uninsulated and thus shall never be operated with power on, for fear of an accident
- The handle is made of wood and thus shall never be knocked with force, for fear of cracking

No.			
03109	20	40	6

▲ Excluded from lifetime warranty terms.