


NON-INSULATED COPPER TUBULAR LUGS (TCL-2A SERIES)



MAXIMUM ELECTRIC CURRENT:

A.W.G.	1	1/0	2/0	3/0	250	500
AMP.	195	230	265	310	405	620

TERMINAL MATERIAL: COPPER TUBULAR

WIRE RANGE A.W.G. mm ²	ITEM NO.	STUD SIZE		DIMENSION mm							CRIMPING TOOL	Q'TY BOX
		2×d2		W	L	E	D	d1	T	A		
1-1/0 A.W.G. 50 mm ²	TCL50-2A10	3/8	10.5	19.3	93.7	36.6	13.2	10.0	3.1	25.4	NOVOPRESS MODEL HPM400	50
2/0 A.W.G. 70 mm ²	TCL70-2A	1/2	13.0	20.2	130.0	40.0	14.0	11.0	2.9	44.5	NOVOPRESS MODEL HPM400	50
3/0 A.W.G. 95 mm ²	TCL95-2A	3/8	10.5	23.2	100.0	30.0	16.0	13.0	3.2	25.4	NOVOPRESS MODEL HPM400	50
250 MCM 150 mm ²	TCL150-2A	1/2	13.0	28.7	135.0	40.0	20.0	15.6	4.3	44.5	NOVOPRESS MODEL HPM400	50
	TCL150-2A-1	9/16	14.0									
500 MCM 300 mm ²	TCL300-2A	9/16	15.0	41.0	155.0	60.0	28.5	22.1	6.3	44.5	NOVOPRESS MODEL HPM400	10

