


DIN 46228

NON-INSULATED CORD END TERMINALS



MAXIMUM ELECTRIC CURRENT:

A.W.G.	8	6	4
AMP.	70	95	125

TERMINAL MATERIAL: COPPER TUBE. (TIN PLATED)

WIRE RANGE A.W.G. mm ²	ITEM NO.	DIMENSION								CRIMPING TOOL
		L		D		C		W		
		inch	mm	inch	mm	inch	mm	inch	mm	
8 A.W.G. 10 mm ²	EN10-16	.630	16.0	.193	4.9	.177	4.5	.228	5.8	K.S. MODEL KST2000M WITH DIE INDEX NO:10
	EN10-18	.709	18.0							
	EN10-20	.787	20.0							
	EN10-22	.866	22.0							
	EN10-25	.984	25.0							
6 A.W.G. 16 mm ²	EN16-6 ©	.236	6.0	.244	6.2	.228	5.8	.299	7.6	K.S. MODEL KST2000M WITH DIE INDEX NO:16
	EN16-8 ©	.315	8.0							
	EN16-12	.472	12.0							
	EN16-15	.591	15.0							
	EN16-16	.630	16.0							
	EN16-18	.709	18.0							
	EN16-20	.787	20.0							
	EN16-22	.866	22.0							
	EN16-25	.984	25.0							
	EN16-30	1.181	30.0							
	EN16-32	1.260	32.0							
4 A.W.G. 25 mm ²	EN25-6 ©	.236	6.0	.303	7.7	.287	7.3	.366	9.3	K.S. MODEL KSTP325-B WITH DIE INDEX NO:E-25
	EN25-8 *	.315	8.0							
	EN25-12 ©	.472	12.0							
	EN25-13 *	.512	13.0							
	EN25-15	.591	15.0							
	EN25-16	.630	16.0							
	EN25-18	.709	18.0							
	EN25-20	.787	20.0							
	EN25-22	.866	22.0							