


DIN 46235

NON-INSULATED COPPER TUBULAR LUGS (TLD SERIES)


MAXIMUM ELECTRIC CURRENT:

A.W.G.	2/0	3/0	4/0	250	300	350
AMP.	265	310	360	405	445	505

TERMINAL MATERIAL: COPPER TUBULAR

WIRE RANGE A.W.G. mm ²	ITEM NO.	DIMENSION mm									CRIMPING TOOL	Q'TY BOX
		a	b	C1	C2	d1	d2	d3	I	S		
2/0 A.W.G. 70 mm ²	TLD8-70	28.0	24.0	13.0	10.0	11.5	8.4	16.5	55.0	4.5	NO OPRESS MODEL HPM400	50
	TLD10-70			15.0	12.0		10.5					50
	TLD12-70			16.0	13.0		13.0					50
	TLD14-70			14.5	14.5		15.0					50
	TLD16-70		30.0	19.0	16.0		17.0					50
3/0 A.W.G. 95 mm ²	TLD8-95	35.0	28.0	12.0	12.0	13.5	8.4	19.0	65.0	5.0	NO OPRESS MODEL HPM400	25
	TLD10-95			15.0	12.0		10.5					25
	TLD12-95			16.0	13.0		13.0					25
	TLD14-95			14.5	14.5		15.0					25
	TLD16-95		32.0	19.0	16.0		17.0					25
4/0 A.W.G. 120 mm ²	TLD10-120	35.0	32.0	15.0	12.0	15.5	10.5	21.0	70.0	5.5	NO OPRESS MODEL HPM400	25
	TLD12-120			16.0	13.0		13.0					25
	TLD14-120			17.5	19.0		15.0					25
	TLD16-120			19.0	16.0		17.0					25
	TLD20-120 *		38.0	22.0	20.0		21.0					25
250/300 MCM 150 mm ²	TLD10-150	35.0	34.0	15.0	12.0	17.0	10.5	23.5	78.0	6.0	NO OPRESS MODEL HPM400	25
	TLD12-150			16.0	13.0		13.0					25
	TLD14-150			18.5	20.0		15.0					25
	TLD16-150			19.0	16.0		17.0					25
	TLD20-150		40.0	22.0	20.0		21.0					25
300/350 MCM 185 mm ²	TLD10-185 *	40.0	37.0	15.0	12.0	19.0	10.5	25.5	82.0	6.0	NO OPRESS MODEL HPM400	10
	TLD12-185			16.0	13.0		13.0					10
	TLD14-185			18.5	20.0		15.0					10
	TLD16-185			19.0	16.0		17.0					10
	TLD20-185 *		40.0	22.0	20.0		21.0					10

*: DEVELOPING ON DEMAND