

3/8" Dr. Bit Socket, Phillips

3/8"



• Bit made from S2 material for durability and anti-slipping

No.	Spec.	L(mm)			
22301	#1	48	6	-	-
22302	#2	48	6	-	-
22303	#3	48	6	-	-

⚠ These bit sockets should never be used on power drivers, pneumatic impact wrench and/or extenders.

3/8" Dr. Bit Socket, Pozidrive

3/8"



• Bit made from S2 material for durability and anti-slipping

No.	Spec.	L(mm)			
22401	#1	48	6	-	-
22402	#2	48	6	-	-
22403	#3	48	6	-	-

⚠ These bit sockets should never be used on power drivers, pneumatic impact wrench and/or extenders.

3/8" Dr. Bit Socket, Slotted

3/8"



• Bit made from S2 material for durability and anti-slipping

No.	Spec. (mm)	L(mm)			
22501	5.5	48	6	-	-
22502*	6.5	48	6	-	-
22503*	8.0	48	6	-	-
22504	4.0	48	6	72	3.9

⚠ These bit sockets should never be used on power drivers, pneumatic impact wrench and/or extenders.



High quality of SATA bits Socket



1. Bit made of high-grade alloy steel (S-2) for durability and anti-slipping
2. Length of 50MM, 100MM or custom one available as required
3. 6-point screwdriver bar inserted into 6-point socket for anti-slipping



4. Cr-V socket joint for high torque
5. Spec. of 6.3MM, 10MM and 12.5MM available

SATA Bit Socket Type



Slotted



Torx®



Hexagon



Phillips



Pozidrive



Triple Square



Tamper-Proof
Torx®