


# NYLON-INSULATED RING TERMINALS

**MAXIMUM ELECTRIC CURRENT:**

|        |    |     |
|--------|----|-----|
| A.W.G. | 6  | 4   |
| AMP.   | 95 | 125 |

**MAXIMUM ELECTRICAL RATING: 105°C 600 VOLTS MAX.**
**INSULATION MATERIAL: NYLON**
**INSULATION COLOR:**

6 A.W.G.: BLUE ■ 4 A.W.G.: YELLOW ■

**TERMINAL MATERIAL: COPPER**


| WIRE RANGE<br>A.W.G.<br>mm <sup>2</sup> | ITEM NO.    |             | STUD SIZE | DIMENSION <small>inch mm</small> |               |              |               |              |              |             | CRIMPING TOOL                                            | Q'TY BOX |
|-----------------------------------------|-------------|-------------|-----------|----------------------------------|---------------|--------------|---------------|--------------|--------------|-------------|----------------------------------------------------------|----------|
|                                         | BRAZED SEAM | BUTTED SEAM | d2        | W                                | F             | L            | E             | D            | d1           | T           |                                                          |          |
| 6 A.W.G.<br><br>14 mm <sup>2</sup>      | RNYB14-4 ■  |             | #8        | .169<br>4.3                      | .472<br>12.0  |              | 1.583<br>40.2 |              |              |             | K.S. MODEL<br>KST-HDC38A<br>WITH DIE INDEX<br>:INS(mm)14 | 250      |
|                                         | RNYBS14-5   |             | #10       | .209<br>5.3                      | .374<br>9.5   |              | 1.543<br>39.2 |              |              |             |                                                          | 250      |
|                                         | RNYB14-5 ■  |             | #10       | .209<br>5.3                      | .472<br>12.0  | .524<br>13.3 | 1.583<br>40.2 |              |              |             |                                                          | 250      |
|                                         | RNYBSS14-6  |             | 1/4       | .252<br>6.4                      | .374<br>9.5   |              | 1.543<br>39.2 |              |              |             |                                                          | 250      |
|                                         | RNYBS14-6 ■ |             | 1/4       | .252<br>6.4                      | .472<br>12.0  |              | 1.583<br>40.2 |              |              |             |                                                          | 250      |
|                                         | RNYBL14-6   |             | 1/4       | .252<br>6.4                      |               |              |               |              |              |             |                                                          | 250      |
|                                         | RNYB14-8 ■  |             | 5/16      | .331<br>8.4                      | .630<br>16.0  | .559<br>14.2 | 1.713<br>43.5 | .846<br>21.5 | .433<br>11.0 | .228<br>5.8 |                                                          | 250      |
|                                         | RNYB14-10   |             | 3/8       | .413<br>10.5                     |               |              |               |              |              | .059<br>1.5 |                                                          | 250      |
|                                         | RNYB14-11   |             | 7/16      | .453<br>11.5                     | .866<br>22.0  | .780<br>19.8 | 2.047<br>52.0 |              |              |             |                                                          | 250      |
|                                         | RNYB14-12   |             | 1/2       | .512<br>13.0                     |               |              |               |              |              |             |                                                          | 250      |
|                                         | RNYB14-14   |             | 9/16      | .591<br>15.0                     |               |              |               |              |              |             |                                                          | 250      |
|                                         | RNYB14-16   |             | 5/8       | .669<br>17.0                     | 1.244<br>31.6 | .996<br>25.3 | 2.441<br>62.0 |              |              |             |                                                          | 250      |
|                                         | RNYB14-18   |             | 11/16     | .748<br>19.0                     |               |              |               |              |              |             |                                                          | 250      |
|                                         | RNYB14-20   |             | 3/4       | .827<br>21.0                     |               |              |               |              |              |             |                                                          | 250      |
| 4 A.W.G.<br><br>22 mm <sup>2</sup>      | RNYBS22-4   |             | #8        | .169<br>4.3                      |               |              |               |              |              |             | K.S. MODEL<br>KST-HDC38A<br>WITH DIE INDEX<br>:INS(mm)22 | 200      |
|                                         | RNYB22-4    |             | #8        | .169<br>4.3                      | .480<br>12.2  | .594<br>15.1 | 1.780<br>45.2 |              |              |             |                                                          | 200      |
|                                         | RNYBS22-5   |             | #10       | .209<br>5.3                      |               |              |               |              |              |             |                                                          | 200      |
|                                         | RNYBL22-5   |             | #10       | .209<br>5.3                      | .650<br>16.5  | .531<br>13.5 | 1.791<br>45.5 |              |              |             |                                                          | 200      |
|                                         | RNYBS22-6   |             | 1/4       | .252<br>6.4                      | .480<br>12.2  | .594<br>15.1 | 1.772<br>45.0 | .945<br>24.0 | .512<br>13.0 | .303<br>7.7 |                                                          | 200      |
|                                         | RNYBL22-6 ■ |             | 1/4       | .252<br>6.4                      | .650<br>16.5  | .531<br>13.5 | 1.791<br>45.5 |              |              | .067<br>1.7 |                                                          | 200      |
|                                         | RNYBS22-8   |             | 5/16      | .331<br>8.4                      | .480<br>12.2  | .594<br>15.1 | 1.780<br>45.2 |              |              |             |                                                          | 200      |
|                                         | RNYB22-8 ■  |             | 5/16      | .331<br>8.4                      | .650<br>16.5  | .531<br>13.5 | 1.791<br>45.5 |              |              |             |                                                          | 200      |
|                                         | RNYB22-10   |             | 3/8       | .413<br>10.5                     |               |              |               |              |              |             |                                                          | 200      |



ALL LISTED

\* : ADDITIONAL CERTIFIED

■ : 90D available

Products can be bend to 90-degrees angle.