


DIN 46228

NON-INSULATED CORD END TERMINALS


MAXIMUM ELECTRIC CURRENT:

A.W.G.	3/0	4/0	250	300	350	400	500	600
AMP.	310	460	405	445	505	545	620	690

TERMINAL MATERIAL: COPPER TUBE, (TIN PLATED)

WIRE RANGE A.W.G. mm ²	ITEM NO.	DIMENSION								CRIMPING TOOL
		L		D		C		W		
		inch	mm	inch	mm	inch	mm	inch	mm	
3/0 A.W.G. 95 mm ²	EN95-25	.984	25.0	.614	15.6	.583	14.8	.681	17.3	K.S. MODEL KSTP325-B WITH DIE INDEX NO:KC-95
	EN95-30	1.181	30.0							
	EN95-32	1.260	32.0							
	EN95-34	1.339	34.0							
4/0 A.W.G. 120 mm ²	EN120-30	1.181	30.0	.697	17.7	.657	16.7	.795	20.2	K.S. MODEL KSTP325-B WITH DIE INDEX NO:KC-120
	EN120-32	1.260	32.0							
	EN120-34	1.339	34.0							
	EN120-38	1.496	38.0							
	EN120-40	1.575	40.0							
	EN120-50	1.969	50.0							
250/300 MCM 150 mm ²	EN150-32	1.260	32.0	.811	20.6	.722	19.6	.906	23.0	K.S. MODEL KSTP325-B WITH DIE INDEX NO:KC-150
	EN150-34	1.339	34.0							
	EN150-35	1.378	35.0							
	EN150-38	1.496	38.0							
	EN150-40	1.575	40.0							
	EN150-60	2.362	60.0							
300/350 MCM 185 mm ²	EN185-25	.984	25.0	.843	21.4	.795	20.2	.941	23.9	K.S. MODEL KSTP325-B WITH DIE INDEX NO:KC-185
	EN185-32	1.260	32.0							
	EN185-40	1.575	40.0							
400 MCM 240 mm ²	EN240-32	1.260	32.0	.953	24.2	.906	23.0	1.043	26.5	K.S. MODEL KSTP325-B WITH DIE INDEX NO:E 240
	EN240-34	1.339	34.0							
	EN240-40	1.575	40.0							
500/600 MCM 325 mm ²	EN325-34	1.339	34.0	1.051	26.7	1.004	25.5	1.102	28.0	K.S. MODEL KSTP325-B WITH DIE INDEX NO:E 325
	EN325-40	1.575	40.0							
600/750 MCM 400 mm ²	EN400-40	1.575	40.0	1.205	30.6	1.150	29.2	1.260	32.0	
800/1000 MCM	EN500-40	1.575	40.0	1.362	34.6	1.307	33.2	1.417	36.0	