


NTN BEARING CORPORATION OF AMERICA

Head Office


1600 E. Bishop Court, P.O. Box 7604

Mount Prospect, IL 60056-7604, U.S.A.

Phone: 847-298-7500

Fax: 847-699-9744


Toll Free: 800-323-2358

Email: mkt@ntnamerica.com
Website: www.ntnamericas.com
Item # UC212D1, Bearing Insert w/ Set Screw, Wide Inner Ring - Spherical O.D.

[Order Now](#) | [Technical Specifications](#) | [Dimensional Specifications](#) | [Specifications](#)
Order Now
Ordering Options
FIND A DISTRIBUTOR
CONTACT NTN CUSTOMER SUPPORT SPECIALIST
ORDER THROUGH NTN DOL (AUTHORIZED DISTRIBUTORS ONLY)
Technical Specifications
Type Insert Bearing

Bore Type Round

Bearing Type	Ball Bearing
Material	Through Hardened Steel
Ball Material	Through Hardened
Limiting Speed - Grease	2500 RPM
Seal Type	Contact
Seal Material	Nitrile Rubber
Precision Rating	ISO Class 0
Performance	Standard Duty
Locking Device	Set Screw
Lubrication	Outer Ring
Basic Outer Ring	212
Clearance	CN
Static Load Rating	36000 N 36.00 kN
Dynamic Load Rating	52500 N 52.50 kN
Enclosure	Double Sealed
Weight	7.390 kg
Operating Temperature Range	-40 to 120 °C

Dimensional Specifications



Bearing Insert w/ Set Screw, Wide Inner Ring - Spherical O.D. - Dimensions

d		60.000 mm
D		110.000 mm
C		27.000 mm
B		65.100 mm
r		2.000 mm
ds		M10x1.25
G		10 mm
d4		77 mm
S1		39.7 mm
S		25.4 mm
F		6.2 mm

Specifications

Radial Dynamic Load Rating	52500 N
Lubrication	Outer Ring
Radial Static Load Rating	36000 N