

DIN 46237


NYLON-INSULATED RING TERMINALS

MAXIMUM ELECTRIC CURRENT:

A.W.G.	16	14	12	10	8
AMP.	18	30	35	50	70

MAXIMUM ELECTRICAL RATING: 105°C 600 VOLTS MAX.
INSULATION MATERIAL: NYLON
INSULATION COLOR:

16-14 A.W.G.: BLUE 12-10 A.W.G.: YELLOW 8 A.W.G.: RED

TERMINAL MATERIAL: COPPER


WIRE RANGE A.W.G. mm ²	ITEM NO.		STUD SIZE		DIMENSION mm						CRIMPING TOOL	Q'TY BOX
	BRAZED SEAM	BUTTED SEAM	d2		d3	l	d1	d4	a	S		
16-14 A.W.G. 1.5-2.5 mm ²	DRNYB4-2.5	DRNY4-2.5	#8	4.3	8.0	18.0	2.3	4.5	11.0	0.8	IZUMI MODEL 34 WITH DIE INDEX COLOR:BLUE OR K.S. MODEL KST2000A HRI-126J WITH DIE INDEX COLOR:BLUE	1000
	DRNYBS5-2.5	DRNYS5-2.5	#10	5.3		19.5						1000
	DRNYB5-2.5	DRNY5-2.5	#10	5.3	10.0	20.0						1000
	DRNYB6-2.5	DRNY6-2.5	1/4	6.5	11.0	22.0						1000
	DRNYB8-2.5	DRNY8-2.5	5/16	8.4	14.0	23.0						1000
	DRNYB10-2.5	DRNY10-2.5	3/8	10.5	15.0							1000
	DRNYBL10-2.5	DRNYL10-2.5	3/8	10.5	18.0	24.5						1000
	DRNYB12-2.5	DRNY12-2.5	1/2	13.0		26.0						1000
12-10 A.W.G. 2.5-6 mm ²	DRNYB4-6	DRNY4-6	#8	4.3	8.0	21.0	3.6	6.4	13.0	1.0	IZUMI MODEL 5 WITH DIE INDEX COLOR:YELLOW OR K.S. MODEL KST2000A HRI-126J WITH DIE INDEX COLOR:YELLOW	500
	DRNYB5-6	DRNY5-6	#10	5.3	10.0	22.0						500
	DRNYB6-6	DRNY6-6	1/4	6.5	11.0	23.0						500
	DRNYB8-6	DRNY8-6	5/16	8.4	14.0	26.0						500
	DRNYB10-6	DRNY10-6	3/8	10.5	18.0	28.0						500
	DRNYB12-6	DRNY12-6	1/2	13.0								500
8 A.W.G. 10 mm ²	DRNYB5-10 [Ⓢ]		#10	5.3	10.0	24.5	4.5	8.0	16.5	1.1	KLAUKE MODEL PK25/2 WITH DIE INDEX NO: HIS 25/10 OR K.S. MODEL KS-HDC38A WITH DIE INDEX NO.:8(INS)	500
	DRNYB6-10 [Ⓢ]		1/4	6.5	11.0	25.5						500
	DRNYB8-10 [Ⓢ]		5/16	8.4	14.0	28.5						500
	DRNYB10-10 [Ⓢ]		3/8	10.5	18.0	29.5						500
	DRNYB12-10 [Ⓢ]		1/2	13.0	22.0	31.5						500



ALL LISTED

[Ⓢ]: NOT UL AND C-UL LISTED