

NYLON-INSULATED RING TERMINALS

MAXIMUM ELECTRIC CURRENT:

A.W.G.	22	20	18	16
AMP.	9	12	17	18


MAXIMUM ELECTRICAL RATING: 105°C 600 VOLTS MAX.

INSULATION MATERIAL: NYLON

INSULATION COLOR:

22-16 A.W.G.: RED

TERMINAL MATERIAL: COPPER



WIRE RANGE A.W.G. mm ²	ITEM NO.		STUD SIZE		DIMENSION ^{inch} _{mm}							CRIMPING TOOL	Q'TY BOX	
	BRAZED SEAM	BUTTED SEAM	d2		W	F	L	E	D	d1	T			
22-16 A.W.G.	RNYB1-2	RNY1-2	#2	.087 2.2	.217 5.5	.197 5.0	.713 18.1	.433 11.0	.157 4.0	.067 1.7	.030 0.75	IZUMI MODEL 34 WITH DIE INDEX COLOR:RED OR K.S. MODEL KST2000A HRI-126J WITH DIE INDEX COLOR:RED	1000	
	RNYB1-2.5	RNY1-2.5	#2	.095 2.4		.189 4.8	.724 18.4						1000	
	RNYB1-3.2	RNY1-3.2 *	#4	.126 3.2		.197 5.0	.728 18.5						1000	
	RNYBS1-3.7	RNYS1-3.7 *	#6	.146 3.7									1000	
	RNYBM1-3.7	RNYM1-3.7 *	#6	.146 3.7	.260 6.6	.248 6.3	.803 20.4						1000	
	RNYBL1-3.7	RNYL1-3.7 *	#6	.146 3.7	.315 8.0	.276 7.0	.858 21.8						1000	
	RNYBS1-4	RNYS1-4 *	#8	.169 4.3	.260 6.6	.248 6.3	.803 20.4						1000	
	RNYBL1-4	RNYL1-4 *	#8	.169 4.3	.315 8.0	.276 7.0	.858 21.8						1000	
	RNYB1-5	RNY1-5 *	#10	.209 5.3									1000	
	0.5-1.5 mm ²	RNYBL1-5	RNYL1-5	#10	.209 5.3	.457 11.6	.433 11.0						1.094 27.8	
RNYB1-6		RNY1-6 *	1/4	.252 6.4	1000									
RNYB1-7		RNY1-7	1/4	.291 7.4	1000									
RNYB1-8		RNY1-8 *	5/16	.331 8.4	.630 16.0		1.433 36.4						1000	
RNYB1-10		RNY1-10 *	3/8	.413 10.5		.535 13.6							.547 13.9	1.240 31.5
RNYBL1-10		RNYL1-10	3/8	.413 10.5	.772 19.6	.543 13.8	1.783 45.3						1000	
RNYB1-12		RNY1-12	1/2	.512 13.0									1000	
RNYB1-13		RNY1-13	9/16	.591 15.0		1.063 27.0	.827 21.0						.031 0.8	
RNYB1-14		RNY1-14	9/16	.591 15.0	1000									
RNYB1-16		RNY1-16	5/8	.669 17.0	1000									
	RNYB1-20	RNY1-20	3/4	.827 21.0										



ALL LISTED

* : ADDITIONAL CERTIFIED

■ : 90D available

Products can be bend to 90-degrees angle.