

VINYL-INSULATED DOUBLE CRIMP FEMALE DISCONNECTORS

MAXIMUM ELECTRIC CURRENT:

A.W.G.	16	14	12	10
AMP.	10	15	20	24

MAXIMUM ELECTRICAL RATING: 105°C 600 VOLTS MAX.

INSULATION MATERIAL: VINYL TERMINAL MATERIAL: BRASS


INSULATION COLOR:

16-14 A.W.G.: BLUE 12-10 A.W.G.: YELLOW

DOUBLE CRIMP: WITH COPPER SLEEVE ON BARREL

TERMINAL BARREL I.D.:

16-14 A.W.G.: C=2.3mm 14-12 A.W.G.: C=2.8mm 12-10 A.W.G.: C=3.4mm



WIRE RANGE A.W.G. mm ²	ITEM NO.	NEMA TAB	DIMENSION ^{inch} / _{mm}						CRIMPING TOOL	Q'TY BOX	
			W	F	L	B	D	T			
16-14 A.W.G. 1.5-2.5 mm ²	FDD2-110(5) *	.020 × .110 (0.5 × 2.8)	.126 3.2	.256 6.5	.748 19.0	.413 10.5	.185 4.7	.012 0.3	IZUMI MODEL 34 WITH DIE INDEX COLOR:BLUE OR K.S. MODEL KST2000A WITH DIE INDEX COLOR:BLUE	1000	
	FDD2-110(8) *	.032 × .110 (0.8 × 2.8)	.197 5.0	.252 6.4	.764 19.4					.014 0.35	1000
	FDD2-187(5) *	.020 × .187 (0.5 × 4.75)									.224 5.7
	FDD2-187(8) *	.032 × .187 (0.8 × 4.75)	.260 6.6	.297 7.5	.819 20.8					1000	
	FDD2-205(5)	.020 × .205 (0.5 × 5.2)								.323 8.2	.394 10.0
	FDD2-205(8)	.032 × .205 (0.8 × 5.2)	.394 10.0	.472 12.0	1.028 26.1						
	FDD2-250 *	.032 × .250 (0.8 × 6.35)								.197 5.0	.256 6.5
	FDD2-312	.032 × .315 (0.8 × 8.0)	.512 13.0	.244 6.2	.917 23.3						
FDD2-375	.047 × .370 (1.2 × 9.4)	.394 10.0				.472 12.0	1.126 28.6	.020 0.5	1000		
12-10 A.W.G. 4-6 mm ²	FDD5-110(5) ©		.020 × .110 (0.5 × 2.8)	.126 3.2	.256 6.5				.866 22.0	.512 13.0	.244 6.2
	FDD5-110(8) ©	.032 × .110 (0.8 × 2.8)	.197 5.0			.256 6.5	.917 23.3	.016 0.4			
	FDD5-187(5)	.020 × .187 (0.5 × 4.75)		.323 8.2	.394 10.0				1.063 27.0	.020 0.5	500
	FDD5-187(8)	.032 × .187 (0.8 × 4.75)	.394 10.0			.472 12.0	1.126 28.6	.020 0.5			500
	FDD5-250 *	.032 × .250 (0.8 × 6.35)		.394 10.0	.472 12.0				1.126 28.6	.020 0.5	500
	FDD5-312	.032 × .315 (0.8 × 8.0)	.394 10.0			.472 12.0	1.126 28.6	.020 0.5			500
	FDD5-375	.047 × .370 (1.2 × 9.4)		.394 10.0	.472 12.0				1.126 28.6	.020 0.5	500

ALL LISTED
 © : NOT UL AND C-UL LISTED
 * : ADDITIONAL CERTIFIED