

## 01511K 12pcs Penumatic shovel and hammer set



- Strong impact
- Variety of accessories
- Suitable for disassembly of chassis, suspension and brake system components
- Suitable for dismantling the car body

No.	Shank hole spec.(mm)	Impact frequency(BPM)	L×W×H(mm)	Unit Weight(kg)			
01511K	φ10	2200	284×52×162	2.2	-	3	17.5

▲ Three-month warranty. Accessories and wearing parts are not covered by the warranty

## 02571 Air Hammer Set



- The set includes: 1 pc Pneumatic Chipping Hammer, 5 pc Medium Carbon Steel Chisel of 175mm in length subjected to heat treatment, 1 pc Spring Fixator, and 1 pc Blow Mold Case
- Cylinder and piston made of alloy steel for long service life
- Power control switch for speed and power output adjustment
- Rear exhaust keeping airflow away from operator and workpiece



No.	Output End Specification	Free Speed (RPM)	Average Gas Consumption (CFM)	Noise Level <sup>2</sup> dB(A)	L×W×H (mm)	Air Inlet Size	Min. Air Hose ID(mm)	Working Air Pressure <sup>3</sup> (Kgf/cm <sup>2</sup> )	Unit Weight(kg)			
02571	10MM Round Bar Chuck	3000 BPM	3	101.4	175×180×50	1/4"	10	6.35	1.58	-	4	16

▲ <sup>1</sup> For tightening capability standard for bolts, refer to bolts with strength level of 12.9 in DIN 267. <sup>2</sup> Noise level is sound pressure of level A. <sup>3</sup> Working air pressure refers to the real-time dynamic air pressure measured at the air inlet of the product during idling operation; <sup>4</sup> Working torque refers to the accumulated torque actually output by the tool running forward for 5 seconds under working pressure; <sup>5</sup> Maximum reversing torque refers to the torque actually accumulated when the tool reverses for 15 seconds under operating air pressure

## Air Blow Gun



97221



97222

- Working air pressure 5.0-8.0KGF/cm<sup>2</sup>
- Brass joint dimensions 1/4"NPT
- Gas flow
- 1/4"-inner-diameter air tube: 350L/min 3/8"-inner-diameter air tube: 430L/min
- Safety precautions
- Wear ear protection, eye protection, work gloves and other personal protective equipment for operation.

No.	Spec. (mm)			
97221	100	5	60	10.6
97222	250	5	50	12.6

▲ Excluded from lifetime warranty terms.