

02523 Composite Air Polisher Set



- Suitable for polishing of work pieces in small or narrow area
- Capable of polishing metal, paint finish or plastic surface, such as car bumper, plastic lamp shell surface, etc
- Fully-enclosed reversing knob for effective dust prevention
- Speed adjustment button for use with only one hand, facilitating speed control
- CVT trigger for continuous fine tuning speed

02524 5" Non-Vacuum Air Random Orbital Sander



- Lightweight and durable composite shell for handiness and comfort
- Low vibration for smoothness and comfort
- Low grinding center of gravity for smooth polishing surface

02525 5" Central Vacuum Air Random Orbital Sander



* Applicable sandpaper



- Used with vacuum cleaning system for collecting impurities and dust
- Lightweight and durable composite shell for handiness and comfort
- Low vibration for smoothness and comfort
- Low grinding center of gravity for smooth polishing surface

01401 Auto 10mm Reversible Air Drill



- Self-locking drill chuck
- Gear reduction mechanism, strong output

02421 3/8" Composite Reversible Air Drill



- Suitable for drilling, hole grinding, reaming, and fraising
- Handle coated with composite, weighting only 0.98KG, with low noise and light weight
- Fully-enclosed reversing knob for effective dust control
- 3/8" Jacobs drill chuck for durability
- CVT trigger for easy initial positioning

02422 3/8" Reversible Air Drill



- High-power industrial-grade air drill suitable for precision drilling, hole grinding, reaming, fraising and wire brush
- Cage-type planetary gear housing for sound transmission and solid spindle support
- Precisely-casted alloy steel cylinder for wear resistance and durability
- CVT trigger for easy initial positioning

No.	Output End Specification	Grinding Disc Specification	Eccentric Distance (mm)	Free Speed (RPM)	Average Gas Consumption (CFM)	Noise Level ² dB(A)	L×W×H(mm)	Air Inlet Size	Min. Air Hose ID(mm)	Working Air Pressure ³ (Kgf/cm ²)	Unit Weight(kg)			
02523	5/16"-24T Main Shaft	3"	-	2200	2.2	83.5	160×147×47	1/4"	10	6.35	0.82	-	5	94
02524	5/16"-24(F)	Self-Adhesive Discs 5"	5	11000	2	80	140×123×103	1/4"	10	6.35	0.80	-	8	9.9
02525	5/16"-24(F)	6-Hole Self-Adhesive Discs 5"	5	11000	2	80	198×123×103	1/4"	10	6.35	0.86	-	8	10
01401	3/8" Drill Chuck	-	-	2000	4	98	202×165.8×42	1/4"	8	6.35	1.21	-	10	14.76
02421	3/8" Drill Chuck	-	-	1800	1.92	83.60	200×148×45	1/4"	10	6.35	0.98	-	10	12.3
02422	3/8" Drill Chuck	-	-	1800	5	78	215×150×44	1/4"	10	6.35	1.20	-	10	14.7

▲ ¹ For tightening capability standard for bolts, refer to bolts with strength level of 12.9 in DIN 267. ² Noise level is sound pressure of level A. ³ Working air pressure refers to the real-time dynamic air pressure measured at the air inlet of the product during idling operation; ⁴ Working torque refers to the accumulated torque actually output by the tool running forward for 5 seconds under working pressure; ⁵ Maximum reversing torque refers to the torque actually accumulated when the tool reverses for 15 seconds under operating air pressure