

Bảng thông số sản phẩm

Thông số kỹ thuật



Bell Switch, AvatarOn A, 10A 250V, E sized H, White

M3T31_HBP_WE

Main

Range of product	AvatarOn A
Product or component type	Bell press switch
Load type	Resistive load Inductive
Colour tint	White (WE)

Complementary

Device presentation	Complete product
Rated current	10 A at 250 V AC 50 Hz
Switch application	Bell switch
Clamping connection capacity	2 x 1.5 mm ² for solid cable(s) 2 x 2.5 mm ² for stranded cable(s) 2 x 4 mm ²
Connections - terminals	Screwless type terminals
Local signalling	Fluorescent (white)
Material	PC: dolly PC 10 % GF: base PC 10 % GF: base cover
Device mounting	Flush
Width	70.1 mm
Height	69.3 mm
Depth	33 mm
Embedding depth	22 mm

Environment

IP degree of protection	IP20
Maximum ambient air temperature for operation	45 °C
Ambient air temperature for storage	-5...60 °C
Operating altitude	<= 2000 m
Relative humidity	0...95 %
Standards	IEC 60669-1

Product certifications	IEC TIS
------------------------	------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.3 cm
Package 1 Width	7 cm
Package 1 Length	7 cm
Package 1 Weight	31 g
Unit Type of Package 2	BB1
Number of Units in Package 2	20
Package 2 Height	8.8 cm
Package 2 Width	18.5 cm
Package 2 Length	26.5 cm
Package 2 Weight	718 g
Unit Type of Package 3	S03
Number of Units in Package 3	120
Package 3 Height	30 cm
Package 3 Width	30 cm
Package 3 Length	40 cm
Package 3 Weight	4.958 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Thay thế được đề xuất