

Bảng thông số sản phẩm

Thông số kỹ thuật



Concept - 16AX 250V 2 Way Standard Switch Module with Fluorescent Locator

3031_2_3M_F_G19

Main

Range	Concept
Product or component type	Switch
Device presentation	Mechanism
Device application	Switch
Colour tint	White
Type of packing	Plastic bag
Quantity per set	1
Sale per indivisible quantity	1
Load type	Inductive: 0...250 W Resistive

Complementary

Device mounting	Flush
Switch function	2-way
Number of modules	1 module S
Number of rocker	1
Actuator	Rocker
Range compatibility	Concept
Fixing mode	Clip-in
Surface finish	Glossy
Surface treatment	Untreated
Rated current	16 AX at 250 V AC 50/60 Hz
Electrical durability	20000 cycles conforming to IEC 60669
Connections - terminals	3 screw terminals
Shape of screw head	Cross slotted
Clamping connection capacity	$\leq 4 \text{ mm}^2$ for rigid or stranded cable(s)
Wire stripping length	12 mm
Local signalling	Locator light (green)
Material	PC: dolly PC: base PC: surround

Height	46 mm
Width	23 mm
Depth	33 mm
Embedding depth	25 mm

Environment

Ambient air temperature for storage	0...60 °C
Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Standards	IEC 60669
IP degree of protection	IP20

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Thay thế được đề xuất