

Bảng thông số sản phẩm

Thông số kỹ thuật



S-Flexi - 16A 3 pin twin socket - L size - white

F1426UEST2M_G19

Main

Range	S-Flexi
Product or component type	Socket-outlet
Device application	Power supply

Complementary

Colour tint	White
Quantity per set	1
Type of packing	Plastic bag
Material	PC (polycarbonate)
[In] rated current	16 A
[Ue] rated operational voltage	250 V AC 50...60 Hz
Network number of phases	1 phase
Outlet standard	IEC 60884-1
Number of gangs	1 gang
Socket number	2
Installation direction	Horizontal/vertical
Device mounting	Flush
Connections - terminals	2.5...4 mm ² screw terminal

Environment

Standards	IEC
Ambient air temperature for operation	-5...40 °C

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes

Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Thay thế được đề xuất