

Bảng thông số sản phẩm

Thông số kỹ thuật



Vivace 1Gang 400W DIMMER, Aluminium silver

KB31RD400_AS

! **Ngừng sản xuất vào:** 03 tháng ba 2022

! **Ngừng sản xuất**

Main

Range	Vivace
Device short name	KB31
Product or component type	Dimmer
Device presentation	Complete mechanism
Colour tint	Aluminium silver

Complementary

Power range	Tungsten filament: 400 W
[Ue] rated operational voltage	220...240 V AC
Network frequency	50 Hz
Number of gangs	1 gang
Connections - terminals	Pillar terminals
Terminal identifier	L Load
Tightening torque	0.4 N.m
Clamping connection capacity	1.5 mm ²
Contacts material	Brass and phosphor bronze
Material	Polycarbonate: grid plate Polycarbonate: surround Nylon: base
Device mounting	Flush
Mounting support	Wall mounted
Fixing mode	By screw M3.5
Fixing center	60.3 mm
Width	87 mm
Height	87 mm
Projecting depth	8 mm
Embedding depth	35 mm

Environment

Ambient air temperature for operation -5...40 °C

Relative humidity 0...95 %

Environmental characteristic Indoor use

Standards IEC 60669-2-1

Packing Units

Unit Type of Package 1 PCE

Number of Units in Package 1 1

Package 1 Height 3.5 cm

Package 1 Width 8.6 cm

Package 1 Length 8.6 cm

Package 1 Weight 123.6 g

Offer Sustainability

Sustainable offer status Green Premium product

REACH Regulation [REACH Declaration](#)

EU RoHS Directive Compliant
[EU RoHS Declaration](#)

Mercury free Yes

China RoHS Regulation [China RoHS declaration](#)
Product out of China RoHS scope. Substance declaration for your information

RoHS exemption information Yes

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)

Thay thế được đề xuất