

Bảng thông số sản phẩm

Thông số kỹ thuật



Concept - 2 Gang 3-Pin Universal Duplex Socket Outlet Module with Shutter

3426UEST2M_G19

Main

Range	Concept
Product or component type	Socket-outlet
Device presentation	Mechanism
Outlet poles configuration	2P + E with shutter
Outlet standard description	With earthing contact
Outlet standard	Universal
Colour tint	White
Type of packing	Flow-pack
Sale per indivisible quantity	1

Complementary

Number of power socket outlets	2
Device mounting	Flush
Ground lug position	Straight 0° position
Fixing mode	Clip-in
Pin number	3
Surface finish	Glossy
Rated current	16 A at 250 V AC 50...60 Hz
Electrical durability	5000 cycles
Connections - terminals	push-in
Clamping connection capacity	1.5...4 mm ² for rigid cable(s) 1.5...4 mm ² for stranded cable(s)
Wire stripping length	12 mm

Environment

Ambient air temperature for storage	-5...50 °C
Dielectric strength	2000 V
Ambient air temperature for operation	-5...35 °C

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Thay thế được đề xuất