

Product datasheet

Specifications



S-Flexi - 16A 250V 2 way switch, M size - White

F50_2M2_WE

Main

Range	S-Flexi
Product or component type	Switch
Wiring device mounting	Flush
Switch function	2-way
Switch application	On/off switching
Load type	Light
Colour tint	White

Complementary

Rated current	16 A at 250 V AC 50/60 Hz
Number of gangs	2 gangs horizontal
Material	PC (polycarbonate): wall
Clamping connection capacity	0.5...1.5 mm ² for solid or flexible cable(s)
Connections - terminals	Pillar terminals
Width	46.55 mm
Height	34.95 mm
Depth	34.97 mm

Environment

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Standards	IEC 60669-1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3 cm
Package 1 Width	3.5 cm
Package 1 Length	3.5 cm

Package 1 Weight 24 g

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Recommended replacement(s)