

Bảng thông số sản phẩm

Thông số kỹ thuật



Vivace 16A International Socket with 2.1A USB, Aluminium Silver

KB42616USB_AS_G19

Main

| | |
|---------------------------|-----------------------------|
| Range of product | Vivace |
| Product or component type | USB charger + socket-outlet |

Complementary

| | |
|--------------------------------|---|
| Range | Vivace |
| Device mounting | Flush 30.5 mm |
| Device presentation | Mechanism |
| Socket additional information | Shuttered |
| Number of power socket outlets | 1 x 2P + E with shutter, UK BS 1363 plug 1 x 2P + E with shutter, China 1 x 2P with shutters, Schuko 1 x 2P with shutters, universal |
| Rated current | Power supply: 13 A 250 V, AC, 50/60 Hz 10 A 16 A |
| Colour tint | Aluminium silver |
| Surface finish | Glossy |
| Surface treatment | Untreated |
| Power consumption in W | 0.075 W |
| Input power | 13.5 W |
| Integrated connection type | 2 USB type A 5 V DC, maximum load current: 2.1 A |
| Material | Polycarbonate: grid plate Polycarbonate: surround Polycarbonate: base cover Nylon + GF: shutter Brass: contact plate Steel coated with zinc chromate: spring Nickel steel: terminal screw |
| Protection type | USB port: over temperature protection with PWM IC circuit (battery charging) Over voltage protection against surges Overcurrent protection |
| Shape of screw head | Panhead |
| Screwdriver shape | Phillips combined |
| Electrical connection | 3 screw terminal 2 x AWG 6 |
| Clamping connection capacity | 2 x 4 mm ² for solid or flexible cable(s) |
| Wire stripping length | 10...12 mm |

| | |
|-------------------------|----------------------|
| Mounting support | Mounting box |
| Fixing mode | By screws M4 x 25 mm |
| Fixing center | 60.3 mm |
| Height | 86 mm |
| Width | 86 mm |
| Depth | 38.9 mm |
| Embedding depth | 30.5 mm |
| Net weight | 0.13 kg |
| IP degree of protection | IP20 |
| Type of packing | Bag |

Environment

| | |
|---------------------------------------|--|
| Operating altitude | <= 2000 m |
| Ambient air temperature for operation | 0...40 °C |
| Ambient air temperature for storage | -5...60 °C |
| Relative humidity | 0...95 % |
| Standards | IEC 60950-1 IEC 62368-1 IEC 61558-2-16 |

Packing Units

| | |
|------------------------------|---------|
| Unit Type of Package 1 | PCE |
| Package 1 Length | 8.6 cm |
| Number of Units in Package 1 | 1 |
| Package 2 Width | 31 cm |
| Package 2 Height | 21 cm |
| Package 2 Weight | 8.1 kg |
| Package 3 Height | 95 cm |
| Package 1 Width | 8.6 cm |
| Package 1 Height | 3.89 cm |
| Package 1 Weight | 135 g |
| Number of Units in Package 2 | 60 |
| Unit Type of Package 2 | BB1 |
| Package 2 Length | 50 cm |

Offer Sustainability

| | |
|----------------------------|--|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | Yes |

China RoHS Regulation

[China RoHS declaration](#)
Pro-active China RoHS declaration (out of China RoHS legal scope)

Environmental Disclosure

[Product Environmental Profile](#)

Thay thế được đề xuất