

Bảng thông số sản phẩm

Thông số kỹ thuật



Zencelo - 250V 10A SINGLE 2 PIN UNI 1M SIZED SKT

84426SUS_WE_G19

Main

Range	ZENcelo
Product or component type	Power socket-outlet
Outlet poles configuration	2P universal
Load type	Resistive
Cover plate colour tint	White

Complementary

Device mounting	Flush Surface
Rated current	10 A at 250 V AC 50/60 Hz
Number of gangs	1 gang
Material	Polycarbonate base Polycarbonate cover
Connections - terminals	Screw terminals
Width	23.2 mm
Height	45.8 mm
Depth	31.69 mm

Environment

Ambient air temperature for operation	-5...40 °C
Ambient air temperature for storage	0...60 °C
Relative humidity	0...95 %, non-condensing (storage) 10...95 %, non-condensing (operating)
Environmental characteristic	UV resistant indoor use
Operating altitude	2000 m
IP degree of protection	IP20
Product certifications	CCC
Standards	GB 2099.1 IEC 60884-1

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Thay thế được đề xuất