

Product datasheet

Specifications



S-Flexi - 16A 250V 2 way switch, L size - White

F50_2M4_WE

Main

Range	S-Flexi
Product or component type	Switch
Wiring device mounting	Flush
Switch function	2-way
Switch application	On/off switching
Load type	Light
Colour tint	White

Complementary

Rated current	16 AX at 250 V AC 50/60 Hz
Number of gangs	1 gang horizontal/vertical
Material	PC (polycarbonate): wall
Clamping connection capacity	0.5...1.5 mm ² for solid or flexible cable(s)
Connections - terminals	Pillar terminals
Width	46.55 mm
Height	70.2 mm
Depth	34.97 mm

Environment

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Standards	IEC 60669-1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.0 cm
Package 1 Width	12.5 cm
Package 1 Length	18.0 cm

Package 1 Weight 770.0 g

Offer Sustainability

Sustainable offer status Green Premium product

REACH Regulation [REACH Declaration](#)

REACH free of SVHC Yes

EU RoHS Directive Compliant
[EU RoHS Declaration](#)

Toxic heavy metal free Yes

Mercury free Yes

RoHS exemption information [Yes](#)

China RoHS Regulation [China RoHS declaration](#)
Pro-active China RoHS declaration (out of China RoHS legal scope)

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)

Recommended replacement(s)