

# Bảng thông số sản phẩm

Thông số kỹ thuật



## Electronic Key Card Time Delay Switch, Silver Bronze

A8431EKT\_SZ

### Main

Range	ZENcelo
Product or component type	Key card switch
Rated current	16 A at 240 V AC
Colour tint	Silver bronze

### Complementary

Status LED	LED
Material	Polycarbonate: base Polycarbonate: grid plate Polycarbonate: surround Polycarbonate: lenses
Load type	Incandescent 16 A Fluorescent 8 AX Motor 8 A
Device mounting	Surface Flush
Connections - terminals	Brass terminal
Clamping connection capacity	1 x 1...4 x 1 mm <sup>2</sup> for solid stranded cable(s) 2 x 2.5 mm <sup>2</sup> for solid stranded cable(s) 1 x 1.5...3 x 1.5 mm <sup>2</sup> for solid stranded cable(s)
Width	70 mm
Height	120 mm
Depth	40.7 mm

### Environment

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	<= 2000 m
Ambient air temperature for storage	0...60 °C
Standards	IEC 60669-2-1
IP degree of protection	IP20

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.3 cm
Package 1 Width	8.8 cm
Package 1 Length	13.2 cm
Package 1 Weight	164.5 g
Unit Type of Package 2	CAR
Number of Units in Package 2	30
Package 2 Height	21 cm
Package 2 Width	32.5 cm
Package 2 Length	50 cm
Package 2 Weight	4935 g
Unit Type of Package 3	PAL
Number of Units in Package 3	240
Package 3 Height	120 cm
Package 3 Width	60 cm
Package 3 Length	80 cm
Package 3 Weight	1194400 g

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>

Thay thế được đề xuất