


1/2" 6PTS STANDARD SOCKET




- ASME B107.5M, DIN 3124, ISO 1174-1, ISO 1711-1, ISO 691
- Maxi-Drive™ system helps reduce fastener rounding
- Chrome vanadium steel
- For manual use



SKU #	Description	L (mm)	D1 (mm)	D2 (mm)	Weight (kg)	Box Qty
STMT72933-8B	1/2" 6 PTS Standard Socket 8mm	38	21.8	12.4	0.045	15
STMT72934-8B	1/2" 6 PTS Standard Socket 9mm	38	21.8	14	0.048	15
STMT72935-8B	1/2" 6 PTS Standard Socket 10mm	38	21.8	15.5	0.048	15
STMT72936-8B	1/2" 6 PTS Standard Socket 11mm	38	21.8	16.7	0.05	15
STMT72937-8B	1/2" 6 PTS Standard Socket 12mm	38	21.8	18	0.053	15
STMT72938-8B	1/2" 6 PTS Standard Socket 13mm	38	21.8	19.2	0.052	15
STMT72939-8B	1/2" 6 PTS Standard Socket 14mm	38	21.8	20.5	0.056	15
STMT72940-8B	1/2" 6 PTS Standard Socket 15mm	38	21.8	21	0.054	15
STMT72941-8B	1/2" 6 PTS Standard Socket 16mm	38	23.3	22.5	0.064	14
STMT72942-8B	1/2" 6 PTS Standard Socket 17mm	38	24	23	0.07	12
STMT72943-8B	1/2" 6 PTS Standard Socket 18mm	38	24.8	23	0.07	12
STMT72944-8B	1/2" 6 PTS Standard Socket 19mm	38	26.3	24	0.074	9
STMT72945-8B	1/2" 6 PTS Standard Socket 20mm	38	26.8	24	0.066	9
STMT72946-8B	1/2" 6 PTS Standard Socket 21mm	38	27.7	24	0.084	9
STMT72947-8B	1/2" 6 PTS Standard Socket 22mm	40	29.8	26	0.098	4
STMT72948-8B	1/2" 6 PTS Standard Socket 23mm	40	30.8	26	0.098	4
STMT72949-8B	1/2" 6 PTS Standard Socket 24mm	40	31.8	26	0.1	4
STMT72950-8B	1/2" 6 PTS Standard Socket 25mm	40	32.8	27	0.115	2
STMT72951-8B	1/2" 6 PTS Standard Socket 26mm	43	33.8	28.8	0.11	2
STMT72952-8B	1/2" 6 PTS Standard Socket 27mm	43	35.8	29.5	0.136	2
STMT72953-8B	1/2" 6 PTS Standard Socket 28mm	43	37.6	30.5	0.142	2
STMT72954-8B	1/2" 6 PTS Standard Socket 29mm	43	37.8	31.5	0.145	2
STMT72955-8B	1/2" 6 PTS Standard Socket 30mm	43	39.8	32.5	0.184	2
STMT72956-8B	1/2" 6 PTS Standard Socket 32mm	43	41.8	34.5	0.23	2
STMT72957-8B	1/2" 6 PTS Standard Socket 34mm	45.5	43.8	36.5	0.3	3
STMT72958-8B	1/2" 6 PTS Standard Socket 36mm	57.2	49.8	38	0.45	2

1/2" 12PTS STANDARD SOCKET



- ASME B107.5M, DIN 3124, ISO 1174-1, ISO 1711-1, ISO 691
- Maxi-Drive™ system helps reduce fastener rounding
- Chrome vanadium steel
- For manual use



SKU #	Description	L (mm)	D1 (mm)	D2 (mm)	Weight (kg)	Box Qty
STMT72959-8B	1/2" 12 PTS Standard Socket 8mm	38	21.8	12.4	0.044	15
STMT72960-8B	1/2" 12 PTS Standard Socket 9mm	38	21.8	14	0.048	15
STMT72961-8B	1/2" 12 PTS Standard Socket 10mm	38	21.8	15.5	0.048	15
STMT72962-8B	1/2" 12 PTS Standard Socket 11mm	38	21.8	16.7	0.05	15
STMT72963-8B	1/2" 12 PTS Standard Socket 12mm	38	21.8	18	0.052	15
STMT72964-8B	1/2" 12 PTS Standard Socket 13mm	38	21.8	19.2	0.052	15
STMT72965-8B	1/2" 12 PTS Standard Socket 14mm	38	21.8	20.5	0.056	15
STMT72966-8B	1/2" 12 PTS Standard Socket 15mm	38	21.8	21	0.054	15
STMT72967-8B	1/2" 12 PTS Standard Socket 16mm	38	23.3	22.5	0.064	14
STMT72968-8B	1/2" 12 PTS Standard Socket 17mm	38	24	23	0.065	12
STMT72969-8B	1/2" 12 PTS Standard Socket 18mm	38	24.8	23	0.07	12
STMT72970-8B	1/2" 12 PTS Standard Socket 19mm	38	26.3	24	0.074	9
STMT72971-8B	1/2" 12 PTS Standard Socket 20mm	38	26.8	24	0.066	9
STMT72972-8B	1/2" 12 PTS Standard Socket 21mm	38	27.7	24	0.068	9
STMT72973-8B	1/2" 12 PTS Standard Socket 22mm	40	29.8	26	0.096	4
STMT72974-8B	1/2" 12 PTS Standard Socket 23mm	40	30.8	26	0.096	4
STMT72975-8B	1/2" 12 PTS Standard Socket 24mm	40	31.8	26	0.100	4
STMT72976-8B	1/2" 12 PTS Standard Socket 25mm	40	32.8	27	0.11	2
STMT72977-8B	1/2" 12 PTS Standard Socket 26mm	43	33.8	28.8	0.120	2
STMT72978-8B	1/2" 12 PTS Standard Socket 27mm	43	35.8	29.5	0.126	2
STMT72979-8B	1/2" 12 PTS Standard Socket 28mm	43	37.6	30.5	0.138	2
STMT72980-8B	1/2" 12 PTS Standard Socket 29mm	43	37.8	31.5	0.14	2
STMT72981-8B	1/2" 12 PTS Standard Socket 30mm	43	39.8	32.5	0.164	2
STMT72982-8B	1/2" 12 PTS Standard Socket 32mm	43	41.8	34.5	0.22	2
STMT72983-8B	1/2" 12 PTS Standard Socket 34mm	45.5	43.8	36.5	0.3	3
STMT72984-8B	1/2" 12 PTS Standard Socket 36mm	57.2	49.8	38	0.45	2