

Bảng thông số sản phẩm

Thông số kỹ thuật



AvatarOn - 10A 250V 2Gang Universal Socket - Wood

E83426U2_WD_G19

Main

Product or component type	Socket-outlet
Device presentation	Complete product
Load type	Resistive
Colour tint	Light wood
Outlet poles configuration	2 x 2P
Outlet standard	Universal

Complementary

Rated current	10 A at 250 V AC 50 Hz
Socket number	2
Clamping connection capacity	1 x 4...2 x 4 mm ² for solid cable(s) 1 x 4...2 x 4 mm ² for stranded cable(s) 1 x 2.5...2 x 2.5 mm ² for solid cable(s) 1 x 2.5...2 x 2.5 mm ² for stranded cable(s)
Connections - terminals	Folded terminal Brass pillar
Material	Polycarbonate grid plate Polycarbonate surround
Device mounting	Surface Flush
Width	86 mm
Height	86 mm
Depth	26.7 mm
Embedding depth	17 mm

Environment

IP degree of protection	IP20
Maximum ambient air temperature for operation	35 °C
Ambient air temperature for storage	-5...45 °C
Relative humidity	0...95 %
Environmental characteristic	No UV resistant
Operating altitude	5000 m

Standards	GB 2099.1
-----------	-----------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.7 cm
Package 1 Width	8.6 cm
Package 1 Length	8.6 cm
Package 1 Weight	75.0 g
Unit Type of Package 2	CAR
Number of Units in Package 2	10
Package 2 Height	9.5 cm
Package 2 Width	19.0 cm
Package 2 Length	19.5 cm
Package 2 Weight	801.0 g

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile

Thay thế được đề xuất