MEASURING AND LAYOUT TOOLS

ACCURACY, DEPENDABILITY & DURABILITY

STANLEY®'s measuring innovation has established STANLEY® as a leading worldwide Tape Rule manufacturer. Our expanded line builds on this great heritage. For example, our new FatMax® Xtreme™ Tape Rules features 13" of blade standout, the longest in the world. We've also improved on classics by adding BladeArmor™ Coating to FatMax® and FatMax® Xtreme™ Tape Rules to extend the life of the blade. And that's only the beginning. Take a look at our tape line and see why after years of innovation, STANLEY®'s Tape quality and durability are unmatched.

WHY STANLEY® SHORT TAPES?

- 1 Blade Stand Out
 - 1-1/4" Wide Tape Rule Blade 40% Longer Standout
 - Selective Cross-Curve Blade -10-15%
 Longer Standout
 - Multi-Catch End-Hook -Top, bottom, side-side catch utility
- 2 Product Durability
 - BladeArmor 2x Longer Life
 - Multi-Layer Blade Armor Blade Life
 - Chemically Bonded Tape Case Elastomer grip – Bi-Mat Grips

- Hi-Vis Mylar Easy to read in low lighting (patent pending)
- Bi-Material Wear Plate 500x Longer Life
- Hook Bend Protection Extends End-hook
- Bi-Material Slide Lock Crush Proof
- 3 Compact Case / Longer Blade Length
 - 1-1/4" Wide Spring & Micro-Hub 10% Smaller case



- I Blade durability: stronger, less/ no breakage
 - New "fiber" co-extrusion process
 - 3/4" Wide Blade
 - 50% more Reinforcing strands (+5x)
 - Low Temp "PVC" (+15 10c)
 - BladeArmor End Reinforcement (+2x)
- 2 Blade Abrasion resistance: print longevity
 - Extruded over-coat Clear PVC (+500%)
- 3 Retraction Speed: Fast
 - Gear Drive 3:1







3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 36 15 24 23 22 22 20 19 18 17 18 15 14 13 12 11 10 3 8 7 6 5 4 3 **ACCURACY**

- When a level is placed on a perfectly level surface, the bubble within the vial is equivalent between
- The accuracy of a level is the measure of maximum lift, over 1 Meter, to bring the bubble dead centre on a perfectly flat and level surface
- Solid Block vials have an Accuracy of 0.5"/inch
- 360° Vials have Accuracy no better than 1.5"/inch

TYPES OF LEVELS

BOX

- Magnetic
- Non-Magnetic


I-Beam

- Magnetic
- Non-Magnetic

TORPEDO

Magnetic





1 - 1 D D D

1 MEASURING & LAYOUT TOOLS



MEASURING TAPE SELECTION GUIDE

		TAPE	CASE		LEN	GTH
SHORT TAPES	STANDOUT	WIDTH	MATERIAL	CASE COLOR	METRIC	IMPERIAL
RubberGrip Tape Rule	rip Tape Rule		ABS/Rubber	Yellow/Black	3m, 3.5m, 5m	-
Global Tape Rule	l Tape Rule		ABS	Yellow	3m, 5m, 8m	10′,16′, 26′
Tylon Tape Rule		1"	ABS/Rubber	Yellow/Black	5m, 8m	16', 26'
LeverLock Tape Rule		1/2", 3/4", 1"	ABS	Yellow/Black	3m, 5m, 8m	10′,16′, 26′
PowerLock Tape Rule	8′	1/2", 3/4", 1"	ABS Chromed	Chrome	3m, 3.5m, 5m, 8m, 10m	10', 12', 16', 26', 33'
FatMax Tape Rule	11′	3/4",1", 1-1/4"	ABS/Rubber	Yellow/Black	5m, 8m, 10m	16', 26', 33'
FatMax Xtreme Tape Rule	13′	1-1/4"	ABS Chromed	Yellow/Black	5m, 8m, 10m	-

	TAPE		CASE		LENGTH		
LONG TAPES	TYPE	WIDTH	MATERIAL	CASE COLOR	METRIC	IMPERIAL	
	Open Reel	1/2"	ABS/Rubber	Yellow/Black	30m, 60m	100′, 200′,	
Fiberglass Long Tape	Closed Reel	1/2"	ABS	Yellow/Black	10m, 15m, 20m, 30m, 50m	50', 100', 165'	
Stainless Steel Long Tape	Closed Case	3/8"	ABS	Yellow/Black	15m, 20m, 30m	50′, 100′	

1 MEASURING & LAYOUT TOOLS





STANLEY® Rubbergrip® Tape Rule

- Exclusive cushion grip built into case for comfortable non-slip and impact resistance
- Lacquered blade for maximum durability
- Improved blade readability with high contrast colour easy to read in all lighting conditions
- Massive bumper designed for increased hook life

	BLADE	LENGTH	BLADE '		
SKU#	feet	meters	inches	mm	BOX/CTN
30-611L	12	3.5	1/2"	12.7	6/36





- Durable blade coating for Long lasting scale protection continually easy to read
- 16" and 19.2" stud center markings simplify framing jobs
- Compact, ergonomic case is 10% smaller than PowerLock® classic tapes, making it perfect for smaller settings
- Double-end Big Hook for great grip and easy measure
- 3-rivet, corrosion-resistant hook moves for accurate inside/outside measurements
- Forward blade lock design simplifies locking and unlocking the blade
- Full rubber case provides sturdy, anti-slip hold and shock resistant

	BLADE				
NEW SKU#	DESCRIPTION	Length	Width	BOX/CTN	
STHT36193	Stanley Tylon Short Tape Rule	3m/10′	13mm	6/36	
STHT36194	Stanley Tylon Short Tape Rule	5m/16′	19mm	6/36	
STHT36195	Stanley Tylon Short Tape Rule	8m/26′	25mm	6/36	

STANLEY® Powerlock® Tape Rule



- Highly resistant chrome plated plastic case
- Belt Clip
- Tru-Zero hook
- Class II Accuracy
- Anti abrasion Mylar® polyester film coated blade for long life

		BLADE LENGTH		BLADE WIDTH		
NEW SKU#	SKU#	feet	meters	inches	mm	Box/CTN
STHT33215-8	33-215-2	12′	3.5	1/2"	13	6/36
N/A	STHT33158-8	16′	5	3/4"	19	6/36
N/A	STHT33428-8	26′	8	1"	25	6/24
STHT33463-8	33-463-2	33′	10	1"	25	6/24

email: enquiries-SEA@sbdinc.com



STANLEY® Contractor Grade™ Open Reel Fiberglass LongTape

- 26 Strand 12mm wide blade
- PVC blades allow wound wet and easily cleaned
- Metric English blade printed both sides
- Bi-material handle and shaped winder for ease of use
- Class III Accuracy
- High-impact ABS case withstands rugged conditions

		BLADE	BLADE LENGTH		NIDTH	
NEW SKU#	SKU#	feet	meters	inches	mm	Box/CTN
STHT34791-8	34-791	100′	30	1/2"	13	2/8
STHT34794-8	34-794	200′	60	1/2"	13	2/8
2-34-777	34-777	330′	100	1/2"	13	2/8



STANLEY® Fiberglass LongTape

- 26 strands, 12mm wide blade
- 2 colour graduations easy to read in all conditions
- High impact, high visibility yellow ABS case
- Handle folds for storage
- Class III Accuracy



NEW SKU#	SKU#	DESCRIPTION	BLADE feet	LENGTH meters	BLADE inches	WIDTH mm	Box/ CTN
STHT34260-8	34-260	LONG TAPE CLOSED	50″	15	1/2"	13	6/60
STHT34262-8	34-262	LONG TAPE CLOSED F/G 30M	100′	30	1/2"	13	6/42
STHT34263-8	34-263	LONG TAPE CLOSED	165′	50	1/2"	13	6/36
STHT34298-8	34-298	FIBERGLASS LONG	-	50	-	13	6/36



STANLEY® Steel LongTape

- 9.5mm wide yellow blade with abrasion resistant polymer coating for durability
- 2 colour graduations easy to read in all conditions
- High impact, high visibility yellow ABS case
- Hook with spurs for ease of use
- Class III Accuracy

NEW SKU#	SKU#	DESCRIPTION	BLADE feet	LENGTH meters	BLADE inches	WIDTH mm	Box/ CTN
STHT34104-8	34-104N	15M/50' STEEL LONG TAPE	50′	15	3/8"	9.5	6/24
STHT34107-8	34-107N	30M/100' STEEL LONG TAP	100′	30	3/8"	9.5	6/24
0-34-105	34-105N	STEEL LONG TAPE 20M	-	20	-	9.5	6/24
0-34-108	34-108N	STEEL LONG TAPE 30M	-	30	-	9.5	6/24