

Bảng thông số sản phẩm

Thông số kỹ thuật



Switch, AvatarOn A, 20A 250V, Double Pole, with LED S sized, White

M3T31_D20N_WE

Main

Range of product	AvatarOn A
Product or component type	Switch
Load type	Resistive load Inductive
Colour tint	White (WE)

Complementary

Device presentation	Complete product
Rated current	20 A at 250 V AC 50 Hz
Switch function	2-pole
Switch application	Control switch
Clamping connection capacity	2 x 1.5 mm ² for solid cable(s) 2 x 2.5 mm ² for stranded cable(s) 2 x 4 mm ²
Connections - terminals	Screwless type terminals
Local signalling	Fluorescent (white)
Material	PC: dolly PC 10 % GF: base PC 10 % GF: base cover
Device mounting	Flush
Width	23.1 mm
Height	69.3 mm
Depth	35 mm
Embedding depth	24 mm

Environment

IP degree of protection	IP20
Maximum ambient air temperature for operation	45 °C
Ambient air temperature for storage	-5...60 °C
Operating altitude	<= 2000 m
Relative humidity	0...95 %

Standards	IEC 60669-1
Product certifications	IEC TIS

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.6 cm
Package 1 Width	2.3 cm
Package 1 Length	7.0 cm
Package 1 Weight	34.0 g
Unit Type of Package 2	BB1
Number of Units in Package 2	20
Package 2 Height	9.1 cm
Package 2 Width	8.9 cm
Package 2 Length	25.5 cm
Package 2 Weight	731.0 g
Unit Type of Package 3	S03
Number of Units in Package 3	240
Package 3 Height	30.0 cm
Package 3 Width	30.0 cm
Package 3 Length	40.0 cm
Package 3 Weight	9.422 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Thay thế được đề xuất