

Bảng thông số sản phẩm

Thông số kỹ thuật



S-Flexi - 16A 250V 2 way switch, S size

F50_2M1_5_WE

Main

Range	S-Flexi
Product or component type	Switch
Wiring device mounting	Flush
Switch function	2-way
Switch application	Electrical circuit control
Load type	Resistive Fluorescent
Colour tint	White

Complementary

Rated current	16 A at 250 V AC 50/60 Hz
Number of gangs	1 gang horizontal/vertical
Material	PC (polycarbonate)
Clamping connection capacity	0.2...2.5 mm ² for rigid or stranded cable(s)
Connections - terminals	2 screw terminals
Width	38 mm
Height	23 mm

Environment

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Standards	IEC 60669-1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	22.0 g
Package 1 Height	3 cm
Package 1 Width	2 cm
Package 1 Length	4 cm

Unit Type of Package 2	BB1
Number of Units in Package 2	36
Package 2 Weight	810.0 g
Package 2 Height	8 cm
Package 2 Width	12.5 cm
Package 2 Length	18 cm
Unit Type of Package 3	CAR
Number of Units in Package 3	360
Package 3 Weight	8542.0 g
Package 3 Height	21 cm
Package 3 Width	27 cm
Package 3 Length	43 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Thay thế được đề xuất