

# Bảng thông số sản phẩm

Thông số kỹ thuật



## Concept - 1 Gang 3-Pin Universal Socket Outlet Module with Shutter

3426UESTM\_G19

### Main

Range	Concept
Product or component type	Socket-outlet
Device presentation	Mechanism
Outlet poles configuration	2P + E with shutter
Outlet standard description	With earthing contact
Outlet standard	Universal
Colour tint	White
Type of packing	Flow-pack
Sale per indivisible quantity	1

### Complementary

Number of power socket outlets	1
Device mounting	Flush
Ground lug position	Straight 0° position
Fixing mode	Clip-in
Pin number	3
Surface finish	Glossy
Rated current	16 A at 250 V AC 50...60 Hz
Electrical durability	5000 cycles
Connections - terminals	push-in
Clamping connection capacity	1.5...4 mm <sup>2</sup> for rigid cable(s) 1.5...4 mm <sup>2</sup> for stranded cable(s)
Wire stripping length	12 mm

### Environment

Ambient air temperature for storage	-5...50 °C
Dielectric strength	2000 V
Ambient air temperature for operation	-5...35 °C

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>

Thay thế được đề xuất