

# Bảng thông số sản phẩm

Thông số kỹ thuật



## Concept - 16AX 250V 1 Way Elongated Switch Module with Fluorescent Locator

3031E1\_2M\_F\_G19

### Main

Range	Concept
Product or component type	Switch
Device presentation	Mechanism
Device application	Switch
Colour tint	White
Type of packing	Plastic bag
Quantity per set	1
Sale per indivisible quantity	1
Load type	Inductive: 0...250 W Resistive

### Complementary

Device mounting	Flush
Switch function	1-way
Number of modules	1 module L
Number of rocker	1
Actuator	Rocker
Range compatibility	Concept
Fixing mode	Clip-in
Surface finish	Glossy
Surface treatment	Untreated
Rated current	16 AX at 250 V AC 50/60 Hz
Electrical durability	20000 cycles conforming to IEC 60669
Connections - terminals	2 screw terminals
Shape of screw head	Cross slotted
Clamping connection capacity	$\leq 4 \text{ mm}^2$ for rigid or stranded cable(s)
Wire stripping length	12 mm
Local signalling	Locator light (green)
Material	PC: dolly PC: base PC: surround

Height	46 mm
Width	23 mm
Depth	33 mm
Embedding depth	25 mm

## Environment

Ambient air temperature for storage	0...60 °C
Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Standards	IEC 60669
IP degree of protection	IP20

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>

Thay thế được đề xuất